



PANAMAX

2 Outlet Multi-Use Surge Protector

MD2

SKU: 12737 UPC: 50616008754

Panamax MD2 2 Outlet Multi-Use Surge Protector safeguards equipment against all surges. In the event of a catastrophic surge such as lightning, it completely disconnects AC power to connected equipment. The Noise Filtration Circuit removes noise and provides clean power.

Features:

- Protect Or Disconnect Circuitry
 - Noise Filtration Circuit
 - Paintable Cover
 - Two Diagnostic Lights
 - Thin Profile
 - Grey Finish
-
- Voltage Protection Rating (UL 1449 3rd Edition, 3,000A): L-N 400V, L-G 500V, N-G 400V
 - Thermal Fusing: Yes
 - Single Pulse Energy Dissipation: 1350 Joules
 - Response Time: <1 ns
 - Protection Modes: L-N, L-G, N-G
 - Protect or Disconnect Circuitry: Yes
 - Peak Impulse Current: 60,000 A
 - Nominal Discharge Current: 3,000 A
 - Maximum Current Rating: 15A (1800 W)
 - Line Voltage: 120 VAC, 50/60 Hz
 - Initial Clamping Level: 200V
 - EMI/RFI Noise Filtration: 50 dB (100 kHz - 1 MHz)
 - Catastrophic Surge Circuit: Yes
 - UL 1449 Rating: 330V
 - Lightning Protection: Yes
 - Approximate Dimensions:
 - Height: 5.25"
 - Width: 3.25"
 - Depth: 1.63"