



## UniFi Access Hub

UA-HUB-US

SKU: 145495    UPC: 817882025720

The Access Hub is a sophisticated, single-door entry mechanism that also manages connected Access Readers. The UniFi Access Hub comes with versatile interfaces, including support for most electric bolts/strikes, magnetic locks, and 12V access accessories such as motion sensors, push buttons, and alarms. The three Ethernet PoE powered reader interfaces minimize need for wiring work and offer a convenient way to add a UniFi G3-Flex surveillance camera for additional security. The seamlessly integrated UniFi Access solution is managed with UniFi Access application. Easily manage users, visitors, schedules, and access policies with the intuitive browser-based interface.

### Features

- Powered by 802.3bt (PoE++) switch
- Three 802.3af PoE ports for UniFi readers and G3 Flex surveillance camera
- 12V powered and dry relays compatible with most locks
- Four inputs for motion sensors, request-to-exit devices and door position switch
- Managed with UniFi Access Application in UDM-Pro
- DIN-rail mounting

Dimensions	190 x 126 x 33 mm (7.48 x 4.96 x 1.29")
Weight	457 g (16.12 oz)
Enclosure Characteristics	Plastic Enclosure with Metal Mount Plate
Mounting Options	DIN Rail
Networking Interface	(4) 1 Gbps Ethernet
Max. Power Consumption	40W
Power Method	802.3bt PoE
Input Terminals	REX - Request to Exit REN - Request to Enter REL - Remote Release DPS - Door Position Sensor
Dry Output Relay Lock Aux	Rated 30VDC, up to 1A Rated 30VDC, up to 1A
Powered Output Relay Lock Aux Line	12VDC, up to 1A 12VDC, up to 0.33A 12VDC, up to 0.33A
LEDs	(1) System, (3) PoE Out, (4) Input (2) Output Relays, (1) 12VDC Out
Buttons	Terminal Blocks, Reset
Operating Temperature	0 to 40° C (32 to 104° F)
Operating Humidity	5 - 90% Noncondensing
Certifications	CE, FCC, IC