



ring

Wired Doorbell Pro X

B093BGXTT

SKU: 62934    UPC: 842861112931

**Ring Wired Video Doorbell Pro 2 X** is our best-in-class doorbell for ultimate performance and protection. See and hear like never before with boosted HD+ video and crisp audio quality. Pinpoint movement with 3D Motion Detection. And with Alexa Greetings, Alexa can speak to visitors and accept deliveries when you can't get to the door. It's the first doorbell to run your front door.

#### Features

- 1536p HD+ Video
- Live View w/Color Night Vision
- Field of View:
  - Head-to-Toe Video
  - 150° Horizontal, 150° Vertical
- Motion Detection
  - Customizable (Drawable) Motion Zones
  - 3D Motion Detection
  - Bird's Eye View
- Two-Way Talk with Audio+
- Works With Alexa
- Hardwired (16-24 VAC)



**Ring X Line**

#### Exclusive benefits:

- Lifetime Ring Protect Basic subscription.\*
- Dedicated tech support.
- 3-year limited warranty.

**Note:** Ring X line is a professional installer only product line which features Ring's Protect Lifetime Basic Plan (Savings of \$30 per device, per year) and a 3 year warranty.

## Specifications:

- Size & Color:
  - Dimensions: 4.49 in. x 1.9 in. x .87 in. (114mm x 49mm x 22mm)
  - Colors: Satin Nickel
- Features
  - Video: 1536p HD+ Live Video, HDR, Live View, Color Night Vision
  - Motion Detection: 3D Motion Detection with Bird's Eye View
  - Field of View: 150° horizontal, 150° vertical
  - Audio: Two-Way Talk with Audio+
- Power
  - Hardwired: Standard doorbell system, Ring plug-in adapter (not included), or Ring hardwired transformer (not included) with 16-24 VAC/24VDC, 10-40VA max, 50/60Hz. No halogen or garden-lighting transformers.
  - Internet Requirements: Requires a minimum upload speed of 1Mbps, but 2 Mbps is recommended for optimal performance
  - Connectivity: 802.11 a/b/g/n/ac @2.4GHz and 5.0GHz
- Installation
  - Estimated Installation Time: ~15 min
  - Operating Conditions: -5°F to 120°F (-20°C to 50°C)
  - Setup Requirement: Standard doorbell system, Ring plug-in adapter (not included), or Ring hardwired transformer (not included) with 16-24 VAC/24VDC, 10-40VA max, 50/60Hz.