



Two-channel 800W @ 4Ohms 70V/140V Power Amplifier

CDi2000

SKU: 132013 UPC: 691991013737

The CDi Series amplifiers are professional tools designed and built for installed sound applications. The series includes four models which are identical except for output power: CDi 1000, CDi 2000, CDi 4000, and CDi 6000. All are rugged and lightweight, and offer unmatched value in their class.

Feature

- Two-channel Power Amplifier
- 800W @ 4Ω, 70V/140V
- Extremely versatile; rated for 2-, 4-, 8-ohm loads and 70V and 140V outputs.
- Switch-mode universal power supply.
- Intuitive front-panel LCD screen for quick, easy configuration.
- Onboard digital signal processing includes crossovers, EQ filters, delay, and output limiting.
- Up to 20 user defined DSP presets are available.

Channels	2
Sensitivity (for full rated power at 8 ohms)	1.4V
Rated Power Output (per channel @ 4 ohms)	800W Stereo
Signal to Noise Ratio (below rated 1 kHz power at 8 ohms)	100 dB (A-weighted)
THD	< 0.5%
Damping Factor (20 Hz to 100 Hz)	> 500
Frequency Response (at 1W, 20 Hz - 20 kHz)	+ 0 dB, -1 dB
Crosstalk (below rated power) 20 Hz to 1 kHz	>70 dB
Input Impedance (nominally balanced, nominally unbalanced)	20 kΩ balanced, 10 kΩ unbalanced
Dimensions (inches) (W x H x D) (depth not including 1.3 inch front panel protrusion)	19 x 3.5 x 12.25
Weight	22.0 lbs
IEC Power Connector	15A