



Back Box For KX7 In-Wall Controller

BB-KX7

SKU: 66074 UPC: 810065000000

Mounting box for installation of the touch control panel RTI KX7. Flanges located on the side for fastening to the wall with a stud. Steel construction. Nine perforated holes for wiring. Black color.

Power	+9VDC to +16VDC, 1A max or PoE (Using Class 3 PoE Ethernet router/injector)
Power Management	Adjustable backlight brightness/power down time
Touchscreen Display	High-brightness color TFT LCD WVGA (800x480 pixels) with 65K colors Integrated high-resolution projected capacitive
Display Size	7.0 in (177mm) diagonal
Display Backlight	LED Backlit, 310nit
Infrared Output Port	200mA output Drives up to 1000 ft (300 m) of wire
Serial Port	RJ-45, RS-232 communication (one-way)
Ethernet Port	10/100 Base-T with Power-over-Ethernet (Using Class 3 PoE Ethernet router/injector)
Wireless Ethernet	802.11b/g
Camera	Color CMOS VGA (640x480)
Microphone	Silicon MEMS
Speakers	Two (2), Stereo 2 Watt, 8ohm
Operating Temperature	+32°F to +122°F (0°C to +50°C)
Operating Humidity	5 Non-condensing
Total System Memory	128M Bytes Flash (non-volatile) memory
Device Capability	Total number of devices is limited only by memory
Macro Capability	Unlimited steps in a single macro Total number of macros is limited only by memory Macro capability on every button
Communications	USB programming port
Video Input	3 BNC Connectors Composite, S-Video or Component analog video inputs NTSC/PAL/SECAM
Enclosure	High-impact molded ABS plastic
Front Plate	High-impact molded ABS plastic
Mounting	Integrated mounting wings, or screws through front plate
Installation Cut-Out (W x H)	7.7 in (195mm) x 5.6 in (143mm)
Outer Bezel (W x H)	8.5 in (217mm) x 5.9 in (151mm)
Total Depth in Wall	1.4 in (36mm), 2.1 in (53mm)with Video Connector
Weight	1.4 lbs (634g)

Warranty	One Year (Parts & Labor)
----------	--------------------------