



Key digital®

4K 18G 2x1 HDMI Switcher with Audio

KD-PRO2X1X

SKU: 61700 UPC: 815996021270

- **Power Supply:** KD-PS12W5VC 5V/2.4A DC power jack, screw-in type
- **IR Remote Control:** KD-RMSWPROK
- **Rack Ears:** 1x long, 1x short rack ear for mounting in full-width rack
- **2x 6-pin terminal blocks** for control, analog audio

Technical: HDMI Input (Each): HDMI Connector, Type A, 19 Pin Female HDMI Output: HDMI Connector, Type A, 19 Pin Female HDMI Bandwidth: TMDs bandwidth 18Gbps DDC Signal (Data): Input DDC Signal - 5 Volts p-p (TTL) HDMI Video/Audio Signal: Input Video Signal - 1.2 Volts p-p 3.5mm Stereo Audio Output: Line level audio on TRS connector. Drives 1 VRMS line audio output with a sampling rate of 192KHz Balanced/unbalanced Audio Output: Line level audio on 6-pin terminal block. Drives 2VRMS line audio output with a sampling rate of 192KHz Digital PCM Audio Output: RCA female for digital audio following SPDIF format (IEC 60958). Supports sampling rate up to 192KHz Digital Optical Audio Output: Toslink optical female for digital audio following SPDIF format (IEC 60958). Supports sampling rate up to 96KHz PCM Max Output Level: 1Vpp on 75 Ω , DC coupling Audio Bandwidth: 20Hz to 20kHz @ 0dBu TND + Noise: 0.33% @0dBu @ 1kHz Wired IR: modulated IR signal input, 0-5V TTL or -10 to +10V Power Supply: KD-PS12W5VC 5V/2.4A, 100-240VAC, 50-60Hz, Interchangeable head, screw-in connector General: Regulation: CE, RoHS, WEEE, EAC Enclosure: Black Meta Product Dimensions: 8.25 x 4.0 x 1.7 (210.82 x 101.9 x 43.96mm) Packaging Dimensions: 10.75 x 8.9 x 2.2 (275 x 225 x 55mm) Product Weight: 0.9 lb Shipping Weight: 2 lb