



ILLUMIVUE™ BY MSTR

4MP IP Turret Camera with NightColor - Black

IP4T-NC-BK

SKU: 160665    UPC: 81993201320


Introducing the Illumivue IP4T-NC-BK 4MP IP Turret Camera with NightColor, a state-of-the-art surveillance solution that brings exceptional image quality and advanced features to safeguard your surroundings day and night. With its cutting-edge technology, this camera sets a new standard for security systems. The IP4T-NC-BK captures crystal-clear images with remarkable detail. Whether you're monitoring your home, office, or any other environment, this camera ensures that every crucial element is captured accurately.

The IP4T-NC-BK stands out with its NightColor technology, offering vivid and true-to-life colors even in low-light conditions. Gone are the days of monochrome night vision. With NightColor, you can see the world in its natural hues, enabling you to identify objects and individuals with ease, day or night.

The IP4T-NC-BK is built to withstand various environmental conditions, ensuring reliable performance even in challenging weather. Its durable construction and IP67 weatherproof rating make it suitable for outdoor deployments, offering peace of mind in any situation.


#### Features

- 4MP IP Turret Camera
- NightColor - Ensures ultra-high image quality in low illumination environment
- 2.8mm @ F1.6 Lens
- 120DB True WDR - Wide Dynamic Range for scenes with high-contrast lighting
- 98ft (30m) Smart IR Range
- Smart Analytics - Supports line cross, intrusion detection (based on human body detection), motion, tampering & audio detection
- Extra Low Light - 0.003 Lux
- Built-in Mic
- Supports 256 G Micro SD card
- 835ft PoE Connection Range
- IP67 protection (Indoor/Outdoor)
- Onvif Support (Profile S, Profile G, Profile T)
- Also available in: [WHITE](#)



## Download the Illumivue App

Access, Set-up, and Manage Illumivue surveillance products through your network via iOS, Android or Windows.



### Camera

#### Sensor

1/3", 4.0 megapixel, progressive scan, CMOS

Camera					
Lens	2.8mm@F1.6				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	63.0	25.2	12.6	6.3
Angle Of View (H)	101.1°				
Angle Of View (V)	55.3°				
Angle Of View (O)	111.1°				
Day/Night	IR-cut filter with auto switch (ICR)				
IR Range	Up to 30m (98ft) IR range				
IR On/Off Control	Auto/Manual				
WDR	120dB				
Edge Storage	Micro SD, up to 256 GB				
Built-in Mic	Supported				

Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
9:16 Corridor Mode	Supported
Motion Detection	Up to 4 areas

Image	
Smart IR	Supported
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise

General	
Certifications	CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15
IP Rating	IP67
Power	DC 12V±25%, PoE (IEEE 802.3af)
Dimensions (Ø x H)	?118 x 95mm (?4.6" x 3.8")

Camera	
Weight	0.35kg (0.77lb)