



ILLUMIVUE[™] BY MSTR

4MP IP Vandal Mini Dome Camera with NightColor

IP4MVD-NC

SKU: 160661 UPC: 81993201290

Introducing the Illumivue IP4MVD-NC 4MP IP Vandal Mini Dome Camera with NightColor, a powerful and rugged surveillance solution designed to protect your premises with exceptional image quality and advanced features. This camera is built to withstand the toughest environments while providing clear and detailed footage, day or night.

The IP4MVD-NC captures crisp and sharp images, ensuring that every detail is captured accurately. Whether you're monitoring a busy office space or an outdoor area, this camera delivers unparalleled visual clarity, allowing you to easily identify critical information.

The IP4MVD-NC is equipped with NightColor technology, enabling you to see vibrant and true-to-life colors even in low-light conditions. Say goodbye to grainy and monochromatic night vision. NightColor preserves the integrity of colors, providing you with accurate visuals, making identification and analysis effortless, even in the dark.

Designed to withstand vandalism and tampering attempts, the IP4MVD-NC features a sturdy and compact vandal-resistant mini dome form factor. Its robust construction and impact-resistant materials ensure durability and reliable performance, making it an excellent choice for high-risk environments.

The Illumivue IP4MVD-NC 4MP IP Vandal Mini Dome Camera with NightColor is a robust and reliable security solution. With exceptional image quality, NightColor technology, vandal-resistant construction, and advanced features, this camera ensures comprehensive surveillance coverage while providing accurate visuals day and night.


Features

- 4MP IP Mini Vandal Dome Camera
- NightColor (0.003 LUX)
- 2.8mm @ F1.6 Lens, 120DB True WDR
- 98ft (30m) Smart IR Distance
- Advanced Analytics - Supports line cross, intrusion, enter area, leave area, face detection, face capture, motion, tampering & audio detection
- Built-In MIC
- Supports 256Gb Micro SD card
- IK10 Vandal Resistant
- Cloud Software Updates
- 835ft PoE Connection Range
- IP67 protection (Indoor/Outdoor)
- Onvif Support (Profile S, Profile G, Profile T)



Download the Illumivue App

Access, Set-up, and Manage Illumivue surveillance products through your network via iOS, Android or Windows.



Camera					
Sensor	1/3", 4.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F1.6				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	63.0	25.2	12.6	6.3
Angle Of View (H)	101.1°				
Angle Of View (V)	55.3°				
Angle Of View (O)	111.1°				
Adjustment Angle	Pan: 0° ~ 90°		Tilt: 0° ~ 68°		Rotate: 0° ~ 360°
Minimum Illumination	Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR				
IR Range	Up to 30m (98ft) IR range				
IR On/Off Control	Auto/Manual				
WDR	120dB				
Edge Storage	Micro SD, up to 256 GB				

Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
9:16 Corridor Mode	Supported

Image	
Digital Noise Reduction	2D/3D DNR

Camera	
Smart IR	Supported
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise

General	
Certifications	CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15
IP Rating	IP67
Power	DC 12V±25%, PoE (IEEE 802.3af)
Dimensions (Ø x H)	?110 x 61mm (Ø4.3" x 2.4")
Weight	0.37kg (0.82lb)