HIKVISION®

16-Port 100 Mbps Smart Managed PoE Switch

DS-3E1318P-EI

SKU: 112076   UPC: 842571000000

The Hikvision DS-3E1318P-EI Smart Managed 16-Port 100 Mbps PoE Switch features easy management and maintenance. You can easily deploy, monitor, and expand your surveillance system anytime and anywhere with our software platforms. You can view the network topology, monitor the health of the network, and receive device alarms in real time, which greatly reduces the cost of network operation and maintenance.

Features

- 16 x 100 Mbps PoE Ports, 2 x Gigabit Combos Uplink
- IEEE 802.3at/af PoE Ports
- Network Topology Management, Alarm Push, Network Health Monitor
- 6 KV Surge Protection for PoE Ports
- AF/AT Camera Can Reach up to 980 ft (300 m) in Extend Mode

Port Number	16 × 100 Mbps PoE RJ45 ports, and 2 × gigabit combos
Port Type	RJ-45 port, full duplex, MDI/MDI-X adaptive
Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab, and IEEE 802.3z
Forwarding Mode	Standard mode (default), Extend mode
High Priority Ports	Ports 1 to 8
Long-Distance Transmission Ports	Ports 1 to 16
MAC Address Table	16 K
Switching Capacity	7.2 Gbps
Packet Forwarding Rate	5.3568 Mpps
PoE Standard	Ports 1 to 16: IEEE 802.3af, IEEE 802.3at
Poe Power Pin	Ethernet cables 1/2/3/6 and 4/5/7/8 provide power supply simultaneously
Maximum Port Power	30 W
PoE Power Budget	230 W
Device Maintenance	Support remote upgrade, recovering default parameters, viewing logs, configuring basic network parameters
Device Status Alarm	Device status, PoE_MAX, and PoE status alarm

KOA