



UniFi Managed Poe+ 250W Switch

US-24-250W

SKU: 16674 UPC: 810354020766

Powerful Enterprise Switch Models The UniFi Switch delivers the forwarding capacity to simultaneously process traffic on all ports at line rate without any packet loss. Total non-blocking throughput: up to 26 Gbps for 24-port models and up to 70 Gbps for 48-port models. **Optical Fiber Connectivity** Two SFP ports support uplinks of up to 10 Gbps. For high-capacity uplinks; each 48-port model includes two SFP+ ports for uplinks of up to 10 Gbps. **Convenient PoE+ Support** The UniFi Switch features auto-sensing IEEE 802.3af/at and 24V passive PoE to power multiple devices on the network. **Total Number of Network Ports:** 24 **Modular:** No Port/Expansion Slot **Details:** 24 x Gigabit Ethernet Network; 2 x Gigabit Ethernet Expansion Slot **Media Type Supported:** Twisted Pair **Ethernet Technology:** Gigabit Ethernet **Network Technology:** 10/100/1000Base-T; 1000Base-X **Number of Total Expansion Slots:** 2 **Expansion Slot Type:** SFP **Number of SFP Slots:** 2 **Layer Supported:** 2 **Manageable:** Yes **Power Source:** Power Supply **Compatible Rack Unit:** 1U **Form Factor:** Rack-mountable **Height:** 1.8 **Width:** 19.1 **Depth:** 11.2 **Weight (Approximate):** 8.16 lb **Green Compliant:** Yes **Green Compliance Certificate/Authority:** WEEE **Limited Warranty:** 1 Year. **Genuine Imported Products from USA.** Prices include Import Custom Duties and Taxes.

Features

- Product Group: Computers & Accessories
- Product: Network Switches & Routers
- Product Brand: Monoprice

General:	
Total Non-Blocking Throughput	26 Gbps
Switching Capacity	52 Gbps
Forwarding Rate	38.69 Mpps
Maximum Power Consumption	250 W
Power Method	100 to 240 VAC, 50 to 60 Hz, Universal Input
Power Supply	AC/DC, Internal, 250 W DC
LEDs	RJ45 Data Ports: PoE, Speed/Link/Activity SFP Data Ports: Speed/Link/Activity
Ethernet Networking Interfaces	24 x 10/100/1000 Mb/s RJ45 Ethernet Ports 2 x 1 Gbps SFP Ethernet Ports
Management Interface	1 x RJ45 Serial Port (Reserved for Future Use), Ethernet In/Out Band
Certifications	CE, FCC, IC
Rackmount	Yes, 1U High
ESD/EMP Protection	Air: ?24 kV, Contact: ?24 kV
Shock and Vibration	ETSI300-019-1.4 Standard
PoE	POE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-) 24 VDC Passive PoE (Pins 4, 5+; 7, 8-) Maximum PoE+ Wattage per Port by PSE: 34.2 W
Voltage Range	802.3at Mode, 50 to 57 V
Maximum PoE Wattage Per Data Port	17 W
Voltage Range	20 to 27 V

System Requirements	Linux, Mac OS X, or Microsoft Windows 7/8 Java Runtime Environment 1.6 (or above) Web Browser: Mozilla Firefox, Google Chrome, or Microsoft Internet Explorer 8 (or above)
Operating Temperature	23 to 104°F (-5 to 40°C)
Operating Humidity	5 to 95%, non-condensing
Dimensions	19.1 x 1.75 x 11.24" (485.04 x 44.45 x 285.6 mm)
Weight	8.16 lb (3.7 kg)
Packaging Info:	
Package Weight	13.0 lb
Box Dimensions (LxWxH)	22.5 x 13.1 x 3.2"