



ILLUMIVUE™ BY MSTR

5MP Vandal Dome Camera with NightColor

IP5VD-NC.2

SKU: 160678 UPC: 81993201325

Introducing the Illumivue IP5VD-NC.2 5MP Vandal IP Dome Camera with NightColor, a state-of-the-art surveillance solution that combines exceptional image quality, durability, and advanced features to provide unparalleled security for your premises. With its cutting-edge technology and robust design, this camera sets a new standard in the field of surveillance.

The IP5VD-NC.2 captures incredibly clear and detailed images, ensuring that every critical aspect is captured with precision. Whether you're monitoring a large area or focusing on specific points of interest, this camera delivers outstanding visual clarity, allowing you to capture important details effortlessly.

The IP5VD-NC.2 incorporates NightColor technology, enabling you to see vibrant and accurate colors even in low-light conditions. No more compromising on image quality during nighttime surveillance. NightColor preserves the integrity of colors, providing you with vivid visuals and enhancing your ability to identify objects and individuals, making surveillance more effective and reliable.

Designed to withstand vandalism and tampering attempts, the IP5VD-NC.2 features a robust and impact-resistant vandal dome form factor. Its durable construction ensures that the camera remains protected even in high-risk environments, making it an ideal choice for areas prone to vandalism or tampering.

The Illumivue IP5VD-NC.2 5MP Vandal IP Dome Camera with NightColor is a cutting-edge security solution that delivers exceptional image quality, durability, and advanced features. Its superior image resolution, NightColor capabilities, vandal-resistant design, and intelligent alerts make it the perfect choice for those seeking top-notch surveillance capabilities.

Features

- 5MP IP Vandal Dome Camera
- 2.8mm @ F1.6 Lens
- 121° Field of view
- NightColor - Delivers color and improved brightness in ultra-low light scenarios
- Extra Low Light - 0.003 Lux
- 120dB true WDR technology enables clear image in strong light scene
- Smart Analytics - Supports line cross, motion, tampering & audio detection
- Ultra 265, H.265, H.264, MJPEG
- Support 9:16 Corridor Mode
- Built-in Mic
- Smart IR, up to 30m (98ft) IR distance
- Supports 265 G Micro SD card
- IK10 vandal resistant and IP67 protection
- Support PoE power supply
- 3-Axis
- Onvif Support (Profile S, Profile G, Profile T)
- Also available in: [BLACK](#)



Download the Illumivue App

Access, Set-up, and Manage Illumivue surveillance products through your network via iOS, Android or Windows.



Camera					
Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F1.6				
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8	63.0	25.2	12.6	6.3
Angle Of View (H)	112.9°				
Angle Of View (V)	59.1°				
Angle Of View (O)	121.2°				
Adjustment Angle	Pan: 3° ~ 360°		Tilt: 0° ~ 68°		Rotate: 3° ~ 360°
Minimum Illumination	Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR				
IR Range	Up to 30m (98ft) IR range				
IR On/Off Control	Auto/Manual				
WDR	120dB				
Edge Storage	Micro SD, up to 256 GB				

Video

Video Compression	Ultra 265, H.265, H.264, MJPEG
9:16 Corridor Mode	Supported

Image

Digital Noise Reduction	2D/3D DNR
-------------------------	-----------

Camera	
Smart IR	Supported
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise

General	
Certifications	UL: UL60950-1 FCC: FCC Part 15
IP Rating	IP67
Power	DC 12V±25%, PoE (IEEE 802.3af)
Dimensions (Ø x H)	7109 x 83mm (Ø4.3" x 3.3")
Weight	0.36kg (0.79lb)