



## 16-Channel M Series 8K NVR (No HDD)

DS-9616NI-M8

SKU: 140587    UPC: 842571000000

Hikvision DS-9616NI-M8 16 Channel M Series 8K NVR with No HDD.

### Includes

- Up to 16-ch IP camera inputs
- Up to 2-ch@32 MP/2-ch@24 MP/4-ch@12 MP/8-ch@8 MP/16-ch@4 MP/32-ch@1080p decoding capacity
- Up to 256 Mbps incoming bandwidth and 256 Mbps outgoing bandwidth
- 2 HDMI (different source) and 2 VGA (different source) interfaces, 8K or dual 4K video outputs
- Supports special cameras, including people counting camera, ANPR (automatic number plate recognition) camera, and fisheye camera
- Advanced streaming technology enables smooth live view in poor network conditions
- Supports RAID 0, 1, 5, 6, 10 and N+M hot spare for even more reliable data storage, effectively avoids data loss risks
- H.265+ compression effectively reduces the storage space by up to 75%
- Dual-stream recording saves bandwidth
- Adopt stream over TLS encryption technology which provides more secure stream transmission service
- Support double verification for playback and downloading
- Provide independent HDMI and VGA outputs
- HDMI video output at up to 8K or dual 4K resolution
- 8 SATA interfaces for HDD connection (up to 14 TB capacity per HDD)
- 1 eSATA interface for HDD connection
- 16-ch synchronous playback
- Support multiple VCA (Video Content Analytics) events
- Configurable special camera smart functions, such as VCA detection (motion, line crossing, intrusion, etc.), heat map, ANPR, and people counting
- POS information overlay on live view and playback, and POS triggered recording and alarm
- 2 self-adaptive 10/100/1000 Mbps Ethernet interfaces
- Hik-Connect & DDNS (Dynamic Domain Name System) for easy network management
- Smooth streaming technology
- Support web access without plug-in

IP Video Input	16-ch
Incoming Bandwidth	256 Mbps
Outgoing Bandwidth	256 Mbps
Audio Output	2-ch, RCA
Two-Way Audio	1-ch, RCA
Decoding Format	H.265+/H.265/H.264+/H.264
Synchronous Playback	16-ch
Decoding Capability	2-ch@32 MP (30 fps)/8-ch@8 MP (30 fps)/16-ch@4 MP (30 fps)/32-ch@1080p (30 fps)
RAID Type	RAID0, RAID1, RAID5, RAID6, RAID10
Network Interface	2, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface
Serial Interface	1 RS-485 (full-duplex), 1 RS-232
SATA	8 SATA interfaces



Capacity	Up to 14 TB capacity for each HDD
Alarm In/Out	16/9
USB Interface	Front panel: 2 × USB 2.0; Rear panel: 2 × USB 3.0
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10% to 90%