

# ELURA

## 2-Channel 60W High Performance Amplifier

AMP50/2

SKU: 160887    UPC: 819932013589



Introducing the Elura Amp50/2 2 Channel 60-Watt Amplifier, the perfect solution for powering your audio system with impressive clarity and performance. Designed with precision and excellence in mind, this amplifier delivers rich sound and reliable power for your home theater, music setup, or professional audio environment.

The Elura Amp50/2 boasts two channels, each capable of delivering a solid 60 watts of power, providing a total of 120 watts of audio prowess. Whether you're enjoying your favorite music, immersing yourself in a movie, or seeking to enhance your professional audio setup, this amplifier ensures a powerful and captivating listening experience.

Crafted with high-quality components, the Amp50/2 amplifier guarantees exceptional sound quality. Its advanced engineering reduces distortion, delivering accurate and detailed audio across all frequencies. From thundering bass to crisp highs, every note is reproduced with stunning clarity and precision.

The AMP 50/2 has 5-way binding posts to make connecting your speaker wire easy and secure. The connector can be used to screw down onto bare wire, or banana jacks, spade connectors or pins. Position and polarity are color coded and marked to avoid phase issues. Be sure to follow and maintain proper polarity and position.

Easily mountable with the [Elura AMP50/2-RACK-KIT Dual Amp Rack Mounting Kit](#)

### Features

- 60W x 2 at 4ohm
- 35W x 2 at 8ohm
- 1U half rack width
- Input sensitivity: 430mV
- Frequency response: 41Hz - 22kHz
- High pass filter: -3dB @ 42Hz
- Signal to Noise Ratio: -90dB

Output Power	60W x 2 @ 4ohm, 35W x 2 @ 8ohm
THD+N	@4/8ohm=1.0%
Input Sensitivity	430mV
Frequency Response	41Hz - 22kHz
High Pass Filter	-3dB @ 41Hz
Signal to Noise Ratio	-90dB
Auto Turn ON:	5mV
Turn OFF Delay	15min
Supply Voltage	AC230V / 50Hz , AC110V / 60Hz
Line Level Inputs/Pass Through Outputs	Stereo RCA
Protection	Shorted Output High Temperature

Current Draw @ rated power	2.4 Amps
Certification	TuV Safety rated
Dimensions	216mm (8.5") W 44.5mm (1.75") H 50mm (2") H (including feet) 218mm (8.6") D (including volume knob & speaker connectors)
Unit Weight	1.4kg (3.1lb)
Rack Mount Option	Standard 19" 1U using supplied rack ears
Dual Rack Mount Option	The Elura AMP50/2-RACK-KIT allows strapping two Elura AMP50/2 units together for standard 19" wide single rack space (1U) mounting.