



75" 3-Channel Passive Sound Bar

Mythos 3C-75

SKU: 151146 UPC: 747192140687



The Mythos Series three-channel sound bars elevate home theater experiences indoors and out. Combining the three front channels of a home theater system in a single cabinet, these ultra-slim, on-wall speakers blend high-performance sound and designer aesthetics in a weather-protected, adjustable-width rigid aluminum enclosure. Mythos Series three-channel sound bars are available in three models.

Features

- For 75" TVs
- On-wall, passive sound bar blends high-performance sound and designer aesthetics
- IP66-rated weather-resistant design is suitable for use outdoors
- 3.5" XTDD woofers and 3.5" XTDD midrange drivers deliver balanced lows and mids
- 1" aluminum oxide dome tweeters deliver precise highs, lifelike realism
- Precision crossovers optimize drivers for full, lifelike sound
- Included VESA and wall-mount brackets provide a seamless appearance
- Slim profile with luxury finishes
- A highly rigid, tuned aircraft-grade aluminum enclosure houses the speaker array, with each channel in its own acoustic chamber
- Mythos three-channel passive sound bars feature two- and three-way driver arrays
- Ultra-stiff, 3.5", anodized aluminum dome woofers and midrange drivers eliminate breakup and broaden dispersion, for crisp, clear sound and a spacious, enveloping soundstage
- Rigid, 1", well-damped Dymension™ Series tweeters deliver smooth extended response, crisp transients, and pin-point imaging, for cohesive, lifelike sound that draws you inside the action

Dimensions (H × D)	6.25 × 1.87 in. (159 × 48 mm)
Adjustable Width (W)	65.8 × 69.2 in. (1671 × 1758 mm)
Symmetrically Adjustable Extensions	3.4 in. (86 mm)
Weight	20 lbs (9.3 kg)
Color / Material	Black anodized aluminum
Grille Material	Micro-perforated powder-coated steel
Tweeter	(3) 1 in. aluminum oxide dome
Midrange	(2) 3.5 in. XTDD aluminum dome
Woofers	(8) 3.5 in. XTDD aluminum dome
Number of Channels	3 (left, center, right)
Frequency Response	100 Hz–25 kHz (-10dB) 120 Hz–20 kHz (-3dB)
Nominal Impedance	4? (8? compatible)
Sensitivity	88dB (2.83V/1m)
Recommended Amplifier Power	80W
IP Rating	P66

Included Accessories	(2) VESA-mount brackets and spacers (1) Wall-mount bracket
----------------------	--