



Mythos Adjustable On-Wall LCR Speaker

Mythos LCR-75

SKU: 151149 UPC: 747192140670

The Mythos® Series LCR on-wall speakers elevate home theater experiences indoors and out. Offering horizontal or vertical wall-mountable solutions for the left, center, or right channel, these low-profile speakers blend high-performance sound and designer aesthetics in a weather protected, adjustable, rigid aluminum enclosure. Mythos Series LCR speakers are available in three models.

Features

- For 75" TVs
- On-wall LCR home theater speakers blend premium sound and designer aesthetics
- IP66-rated weather-resistant design is suitable for use outdoors
- 3.5" XTDD woofers and midrange drivers produce balanced lows and mids
- 1" aluminum oxide dome tweeter delivers precise highs, vivid realism
- Precision crossovers optimize drivers for full, lifelike sound
- Mount vertically or horizontally (mount included) for a seamless system look
- Timbre-matched for cohesive sound alongside Definitive Technology speakers
- Slim profile and luxury finishes
- A highly rigid, tuned, aircraft-grade aluminum enclosure ensures the truest sound, uncolored by cabinet resonances, for pristine sonic reproduction
- Mythos LCR on-wall speakers feature 2- and 3-way driver arrays
- Ultra-stiff, 3.5" anodized aluminum dome woofers and midrange drivers eliminate breakup and broaden dispersion, for crisp, clear sound and a spacious, enveloping soundstage
- A 1", rigid, well-damped Dymension™ Series tweeter delivers smooth extended response, crisp transients, and pinpoint imaging, for cohesive, lifelike sound that draws you inside the action
- Timbre-Matched

Dimensions (H x D)	6.25 x 1.87 in. (159 x 48 mm)
Adjustable Width (W)	37.7 x 41.1 in. (958 x 1047 mm)
Symmetrically Adjustable Extensions	3.42 in. (87 mm)
Weight	12 lbs (5.5 kg)
Color / Material	Black anodized aluminum
Grille Material	Micro-perforated powder-coated steel
Tweeter	(1) 1 in. aluminum oxide dome
Midrange	(2) 3.5 in. XTDD aluminum dome
Woofers	(4) 3.5 in. XTDD aluminum dome
Number of Channels	1
Frequency Response	100 Hz–25 kHz (-10dB) 120 Hz–20 kHz (-3dB)
Nominal Impedance	4? (8? compatible)
Sensitivity	88dB (2.83V/1m)
Recommended Amplifier Power	60W
IP Rating	IP66



Included Accessories	(1) Wall-mount bracket
----------------------	------------------------