



# ELURA

## 8" Coaxial Two-Way Pendant Speaker

G8PEND-BK

SKU: 161079    UPC: 81993201418

The Elura line of pendant speakers offers two full-range 2-way products and one subwoofer suited for a wide variety of foreground and background applications such as restaurants, retail, concourses, transportation terminals, worship facilities, etc. All three products are designed to work with 8 Ohm or 70/100V amplifiers with a wide variety of transformer settings for the desired sound level requirement.

Typically, when connecting a 70/100V system, speaker wiring is run from the amplifier location to the first speaker location. The Elura Pendant speakers all come with a 4-Pin Phoenix connector that make it convenient to “loop” the connection from one speaker to another. In a typical 8 Ohm system, each speaker is directly connected to the amplifier (usually only one due to impedance and power demands).

Features

- 2-Way Pendant Loudspeaker
- 8" Fiberglass Woofer with Rubber Surround
- 0.75" Black Aluminium Tweeter with Neodymium Magnet
- Speaker Dispersion Angle: 110° Conical
- Frequency Response: 45HZ-20KHz ± 3db
- Power: 120 watts RMS
- 5/10/20/30W 70V taps plus an 8? bypass
- Aluminum Grille (Non-removable)
- Dimensions: 10.63" x 15.25"

	<a href="#">G6.5PEND-BK</a>	<a href="#">G8PEND-BK</a>	<a href="#">G8PENDSUB-BK</a>
Description	6.5" Coaxial, 2-way pendant loudspeaker	8" Coaxial, 2-way pendant loudspeaker	8" Pendant subwoofer
Woofer Size	6.5 inch	8 inch	8 inch
Woofer Material	Fiberglass cone with rubber surround	Fiberglass cone with rubber surround	Fiberglass cone with rubber surround
Woofer Voice-Coil Size	30.5mm	30.5mm	38.5mm
Tweeter Size	0.75 inch	0.75 inch	n/a

<b>Tweeter Material</b>	Black aluminium	Black aluminium	n/a
<b>Tweeter Magnet</b>	Neodymium	Neodymium	n/a
<b>Recommended Amplifier Power</b>	80 watts RMS	120 Watts RMSI	150 watts RMS
<b>Frequency response</b>	60Hz-20KHz ± 3db	45HZ-20KHz ± 3db	45Hz - 500Hz ± 3db
<b>Sensitivity level</b>	89db @ 1W at 1 meter	91db @ 1W at 1 meter	89db @ 1W at 1 meter
<b>Transformer taps &amp; Thru Setting</b>	5W/10W/15W/20W 70V taps 8Ohm bypass	5W/10W/20W/30W 70V taps 8Ohm bypass	15W/30W/45W/60W 70V taps 8Ohm bypass
<b>Speaker dispersion angle (-6dB)</b>	130° Conical (500Hz-5kHz average)	110° Conical (500Hz-5kHz average)	Omni (45Hz-500Hz)
<b>Grille</b>	Push-On Aluminium	Push-On Aluminium	Push-On Aluminium
<b>Dimensions (W x D x H)</b>	9" x 13.15"	10.63" x 15.25"	10.63" x 15.25"
<b>Weight</b>	8.4 lb (5.25kg)	12.3 lb (5.6kg)	12.3 lb (5.6kg)