



## Evolution 8K HDMI 2X2 SWITCHING SPLITTER

EVSP8K22

SKU: 141484    UPC: 741835000000



The Evolution by Vango EVSP8K22 HDMI Splitter with 8K HDR pass-through, splits one source at a time to two displays. With two HDMI inputs, two 8K sources can be switched and split at the same time. Supports video resolutions up to 8K@60Hz and 4K@120Hz over 4 channels of 10Gbps FRL for 40Gbps bandwidth. Features advanced EDID management and automatically adjusts for EQ based on the HDMI cables connected. Includes an IR remote for control with the option of front panel switching. Able to be used either as a splitter or a switcher, and is a great solution for gaming, video conferencing, education, and more!

**\*To maintain 8K resolution, both displays must have 8K resolution capability as the splitter does not downscale on individual outputs.**

- Transmits audio and video from one of 2 HDMI inputs to 2 HDMI outputs, up to 8K resolution, without any loss of quality or resolution
- Supports video resolutions up to 8K@60Hz 4:2:0 10bit, 8K@30Hz 4:4:4 10bit, 4K@120Hz 4:4:4 10bit
- Supports HDR, HDR10, HDR10+, Dolby Vision, HLG pass through
- VRR, FVA, ALLM supported
- HDMI 2.1 and HDCP 2.3 compliant
- 40Gbps video bandwidth
- HDMI audio formats include LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD
- Built-in Equalizer with advanced manual EDID management
- Controllable via included IR remote and/or front panel switching
- Compact design for easy and flexible installation
- Dimensions: 5.7 W x 2.6 D x .6 H (145mm x 68mm x 17mm)

### Package Contents:

- (1) EVSP8K22 2x2 HDMI Switching Splitter
- (1) IR Remote
- (1) 5V/2A Power Adapter
- (1) Product Manual

Specifications • Transmits audio and video from one of 2 HDMI inputs to 2 HDMI outputs, up to 8K resolution, without any loss of quality or resolution • Supports video resolutions up to 8K@60Hz 4:2:0 10bit, 8K@30Hz 4:4:4 10bit, 4K@120Hz 4:4:4 10bit • Supports HDR, HDR10, HDR10+, Dolby Vision, HLG pass through • VRR, FVA, ALLM supported • HDMI 2.1 and HDCP 2.3 compliant • 40Gbps video bandwidth • HDMI audio formats include LPCM, Dolby Digital/Plus/EX, Dolby True HD, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD • Built-in Equalizer with advanced manual EDID management • Controllable via included IR remote and/or front panel switching • Compact design for easy and flexible installation • Dimensions: 5.7" W x 2.6" D x .6" H (145mm x 68mm x 17mm)