



5MP Turret Varifocal Camera

5MPTEZW

SKU: 23688

The Karbon Vision 5MP Turret Varifocal Camera 5MPTEZW provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video. EXIR 2.0 is Hikvision's proprietary IR extended range technology, which has a range of 130 feet (40 meters). The 2.7 mm to 13.5 mm motorized vari-focal lens is optimized for viewing angles that fit any situation. DWDR (Digital Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.

Features

- 5 MP High Performance CMOS
- Up to 2560 x 1944 Resolution
- 2.7 mm to 13.5 mm Motorized Vari-Focal Lens
- 3D DNR, DWDR
- EXIR 2.0 up to 130 ft (40 m) IR Range
- Multiprotocol Output: TVI/AHD/CVI/CVBS
- Up-the-Coax (HIKVISION-C)
- IP67 Protection

Camera Image Sensor 5 MP progressive scan CMOS Resolution 2560 (H) x 1944 (V) Minimum Illumination Color: 0.01 Lux @ (Æ' 1.2, AGC on), 0 Lux with IR Shutter Speed 1/30 s to 1/50, 000 s Lens 2.7 mm to 13.5 mm motorized vari-focal lens Horizontal Field of View 95.7° to 29.1° Lens Mount Î; 14 Day / Night IR cut filter Angle Adjustment Pan: 0° to 360°; tilt: 0° to 75°; rotate: 0° to 360° Synchronization Internal synchronization Frame Rate 5 MP @ 20 fps, 4 MP @ 30 fps, 1080p @ 30 fps Menu AGC Supported Day/Night Mode Auto/color/BW (black and white) White Balance ATW/MWB BLC Supported DWDR Supported Language English Functions Brightness, sharpness, DNR, mirror, smart IR Interface TVI Video Output 1 HD analog output Switch Button TVI/AHD/CVI/CVBS General Operating Conditions -40° F to 140° F (-40° C to 60° C), humidity: 90% or less (non-condensation) Power Supply 12 VDC ± 25% Power Consumption Maximum 6.3 W Protection Level IP67 Material Metal IR Range Up to 130 ft (40 m) Dimensions 4.88" x 5.29" x 4.38" (123.86 mm x 134.3 mm x 110.11 mm) Weight Approximately 1.28 lbs (580 g)