



1x2 4K HDR HDMI Splitter

SP-0104-H2

SKU: 20613

The latest addition to the WyreStorm Essentials splitter range, the EXP-SP-0104-H2 now offers H2 features and the same value and reliability found in its predecessor, not to mention a few new tricks up its sleeve! Upgrades to support of the full 18Gbps bandwidth HDMI 2.0 offers; 2160p@60Hz 4:4:4 and support for Dolby Vision included. As if that wasn't enough, the EXP-SP-0104-H2 is now featuring a powerful built-in scaler, allowing users to simultaneously connect a mix of 4K and 1080p displays, which gives the source range to play to its fullest potential!

Features

- Allows a transmission from a single HDMI audio/video device to be duplicated and simultaneously distributed to up to four HDMI display devices, such as TV, AVR, digital signage panel or digital projector
- Supports 4K@60Hz 10bit 4:2:0 | 4:4:4 and HDR@24Hz 10bit BT.2020
- Fully HDCP 2.2 compliant
- Data rates up to 18Gbps
- HDR and Dolby Vision support
- Each HDMI output supports scaling down to 1080p
- Automatic input cable equalization for signal regeneration
- DTS-X and Dolby Atmos supported
- Plug and play set up for easy installation no set up / drivers / software required
- Compact, durable design for unobtrusive installation

AUDIO AND VIDEO Inputs 1x HDMI In 19-pin HDMI type A Outputs 4x HDMI Out 19-pin HDMI type A Audio Formats 2ch PCM | Multichannel: LPCM and Up to DTS-X and Dolby Atmos Video Resolutions (Max) 1920x1080p @60Hz 12bit 1920x1080p @60Hz 16bit 3840x2160p @24Hz 10bit 4:2:0 HDR 3940x2160p @30Hz 8bit 4:4:4 3840x2160p @60Hz 10bit 4:2:0 HDR 4096x2160p @60Hz 8bit 4:2:0 4096x2160p @60Hz 8bit 4:4:4 15m/49ft Supported Standards DCI | RGB | HDR | HDR10 | Dolby Vision up 30Hz | HLG | BT.2020 Maximum Pixel Clock 600Mhz COMMUNICATION AND CONTROL HDMI HDCP 2.2 | EDID | DVI-D supported with adapter (not included) POWER Power Supply 5V DC 1A Max Power Consumption 1.8W ENVIRONMENTAL Operating Temperature 32°F ~ 113°F (0°C ~ 45°C) 10% ~ 90%, non-condensing Storage Temperature -4°F to ~ 158°F (-20°C ~ +70°C) 10% ~ 90%, non-condensing Maximum BTU 6.14 BTU/hr DIMENSIONS & WEIGHT Rack Units/Wall Box <1U Height 20mm/0.79in Width 140mm/5.5in Depth 65.2mm/2.57in Weight 0.24kg/0.53lbs REGULATORY Safety and Emission CE | FCC | RoHS | RCM