



Universal Electric Door Strike for Metal and Wood Doors

SD-996C-NUQ

SKU: 27599 UPC: 676544000000

The SECO-LARM® Universal Door Strike can be used with virtually any cylindrical-locking system and can be configured for use in wood, aluminum, or metal doors. Included are three different-sized faceplates that can be easily installed on the strike to match the specific type of door frame.

Features

- UL 294 & UL 1034 Listed
- Includes 3 faceplates for nearly any door type
- Field-selectable for fail-safe or fail-secure operation
- Field-selectable dual-voltage 12/24 VDC operation
- Powered by a solenoid
- Reversible non-handed design fits either right-hand or left-hand doors
- Low profile: Strike is only 1-1/4" deep for use with hollow aluminum frames

Specifications Operating Voltage 12 or 24 VDC $\pm 15\%$ Operation Fail-secure or fail-safe Current Draw 280mA@12VDC, 140mA@24VDC Jaw Strength 2,000-lb Operating Temperature 14°F~113°F (-10°~45° C) Operating Humidity 85% \pm 15% Dimensions - Aluminum 4-7/8" x 1-1/4" (124x32 mm) Dimensions - Hollow Metal 4-7/8" x 1-1/4" (124x32 mm) Dimensions - Wood 7-15/16" x 1-7/16" (202x37 mm)