



Surface Mount

1834-080

SKU: 5723 UPC: 1834-080

The Model 1834 is an ideal telephone entry system suited for apartment and gated community applications as well as office buildings and industrial sites that have a separate access control system, or require telephone entry only. Each 1830 Series unit allows Voice and Data connection over either Cellular, VoIP or POTS. DKS offers easy ways to connect fast using the DKS IM Server and DKS Cellular services. The single-line LCD display features big 1/2-inch characters for easy viewing and your personalized message scrolls across the screen from right to left when the system is not in use. Our unique "One Touch" CALL button and big A and Z scroll buttons makes this system one of the easiest to use on the market today! For additional security, the 1834 allows you to monitor activity AS IT HAPPENS on your computer display.

Features

- Large easy to use A and Z scroll buttons.
- One Touch "CALL" button.
- Built-in single-line LCD directory display.
- Programmable directory codes (1-4 digits).
- 10 and 11-digit dialing capability.
- Live Streaming.
- Live transactions.
- 8000 event transaction buffer.
- Database import/export capability.
- LED Lighting illuminates keypad.
- Built-in clock/calendar.
- Holiday schedule.
- Hold open time zones.
- Built-in postal lock provision.

True Full Duplex Communication. Stores up to 3000 telephone numbers and names (names are limited to 15 characters max). Stores up to 255 area codes. Transaction buffer stores last 8000 events. 8 hold open time zones. 4-digit entry codes, one for each telephone number. 2 form "C" dry contact relays. Single-line directory display uses super-twist LCD with 1/2-inch characters. EEPROM memory chip. Requires touch-tone, loop-start central office phone line. 16 VAC, 20 VA power transformer supplied. FCC (US): DUF6VT-12874-OT-T DOC (CAN): 1736 4528 A Compliant with UL 294. ETL listed. Dimensions Surface Mount: 13"H x 11.25"W x 4.75"D. Dimensions Flush Mount: 13.25"H x 12"W x 3.25"D.