



IP Door Chime

A1061W

SKU: 65491

The DoorBird IP Door Chime is extremely versatile and aesthetically designed to fit in your home. The chime is an ideal addition to every DoorBird door station. It can be flexibly installed on a wall or the ceiling of your home. The connection of the door chime to the network can be made via WiFi or via network cable. The chime can also be powered conveniently via Power-over-Ethernet (PoE). The network-based door chime is configured via the DoorBird App. In addition to the volume and the multiple ringtones it is also possible to set the door chime to a do not disturb mode (individual time ranges*). A DoorBird door station can be connected to an unlimited number of door chimes and the door chime supports an unlimited number of door stations. A separate ringtone can be assigned for every DoorBird door station. The door chime can also operate exclusively over the local area network (LAN) if the Internet has failed in the short term. In addition, a story-call button can be connected to the door chime via a two-wire cable, and, an individual ringtone profile can be configured for this purpose. The resident always knows immediately if the doorbell got pushed at the main door or the apartment door.

Features

- Works online and offline
- Multiple ringtones available (50+)
- Unlimited range works anywhere
- Easy to hear, discrete design
- Made in Germany

Dimensions 125 x 119 x 26 mm (H x W x D) 4,92 x 4,68 x 1,02 in (H x W x D) Power supply 15 V DC or Power over Ethernet (PoE 802.3af Mode-A) Operating conditions 0 to +55°C / 32 to 131°F Relative Humidity 10% to 85% (non condensing) Connectors 1 x RJ45 jack (10/100 Base-T) 4 x Screw terminal Loudspeaker 102 dB WiFi 2.4 GHz, 802.11 b/g/n, internal antenna PoE IEEE 802.3 af/at Housing Polycarbonate, UV-resistant System requirements Mobile Device: Newest iOS on iPhone/iPad, newest Android on Smartphone/Tablet Internet: High-Speed Landline Broadband Internet connection, DSL, Cable or fiber optic, no socks or Proxy server Network: 802.11 b/g/n 2.4 GHz or Ethernet Network, with DHCP Compatible with all DoorBird IP Video Door Stations. Scope of delivery 1 x IP Door Chime 1 x Network Cable 1 x Power supply unit (mains adaptor) with four country-specific adaptors (110 - 240 V AC to 15 V DC) 1 x Small parts 1 x Installation manual Approvals CE, FCC, IC, RoHS, IP50 Weight 200 g EAN 4260423860353