



360° Ceiling Mount Passive Infrared Motion Detector

FX-360

SKU: 112662 UPC: 788924000000

The FX-360 ceiling-mount detector with its unique, highly durable spherical lens offers unparalleled 360° detection performance. False alarm protection technologies, such as RFI Protection, Temperature Protection, and Noise Reduction, come as standard, giving the FX-360 the most unbeatable reliability in its class. The FX-360 is extremely cost-effective and its sleek and compact design suits all types of installation applications.

Features

- Ceiling Mount with Unparalleled 360-degree Detection Performance
- Originally Designed Hard Spherical Lens
- RFI Immunity 20V/m
- Patented Multi-Focus Lens
- Selectable Pulse Count: 2 or 4
- LED On/Off Switch
- Tamper Switch
- Improved EMI
- UL/ULC Listed

Model-FX-360 Detection method-Passive Infrared Coverage-08m~ 012m(025ft. ~ 040ft.) Detection zones -Height: 2.4m ~ 3.6m(8ft. ~ 12ft.) 62 zones Sensitivity-1.6°C(3°F) at 0.6m/sec.(2ft./sec.) Detectable speed-0.3 ~ 1.5m (1 ~ 5ft./sec./sec.) LED indicator -LED blinks during the warm-up period Alarm condition Alarm period -2.0+0.5sec. Alarm output-N.C. 28V DC 0.2A max. C. Opens when the cover is removed. Pulse count -20"±5sec. 2 or 4 Warm-up period- Approx. 30sec. (LED blinks) Power input-9.5 ~ 18V DC Current draw-17mA/(normal) 18mA/(max.) Weight- 140g(4.900z.) Operating temperature -20°C ~ +50°C(-4°F ~ +122°F) Environment humidity -95% max. F interference -No Alarm 20 V/m