



A1101 IP Video Indoor Wall Station - White

423860902

SKU: 65487 UPC: 4260423860902

The DoorBird IP Video Indoor Station is an ideal addition to any DoorBird system. When paired with our DoorBird IP Video Door Intercom, the Indoor Station delivers a live video stream, two-way audio communication as well as control of doors and gates. The Indoor Station is compact and designed to complement any environment.

Features

- WiFi / LAN connection (PoE capable)
- 4" True Color Touch Display
- 2-way HD Audio, up to 102 dB
- Room to room communication
- SIP support
- Home and building automation control
- 3 freely configurable bistable switching relays
- Door opener and elevator control
- Visitor history (free Cloud Recording)
- Room to room communication, when using several Indoor Stations
- SIP support, e.g. for concierge or facility manager calls
- Weather forecast display
- Home and building automation control (IP, TCP, HTTPS, relays etc.)
- Configurable via the DoorBird App worldwide

General

| | |
|----------------------|--|
| Mounting type | Surface-mounted, Table Stand "A8003" sold separately |
| Power supply | 15 – 48 V DC (max. 15 W) or Power over Ethernet (PoE 802.3af Mode-A) |
| Weight | 336 g |
| Connectors | LAN/PoE (T+, T-, R+, R-) Digital input (0 V, 0 A (NO)) #1, e.g. for storey-call button Digital input (0 V, 0 A (NO)) #2, e.g. for second storey-call button Bi-stable latching relay #1, max. 24 V DC / AC, 1 Ampere, e.g. for electric door opener or elevator Bi-stable latching relay # 2, max. 24 V DC / AC, 1 Ampere, e.g. for electric door opener or elevator Bi-stable latching relay # 3, max. 24 V DC / AC, 1 Ampere, e.g. for electric door opener or elevator 15 – 48 V DC input (+, -), max. 15 W |
| Power consumptions | 5 W |
| Approvals | CE, FCC, IC, RoHS, IP50 |
| Dimensions | 179.5 x 115 x 25 mm (H x W x D) 7.07 x 4.53 x 0.98 in (H x W x D) |
| Operating conditions | 0 to +55°C / 32 to 131°F Humidity 0 % to 85 % (non condensing) |

| | |
|-------------------|--|
| Scope of delivery | 1 x IP Video Indoor Station 1 x Mounting bracket 1 x Power supply unit (main adaptor) with four country-specific adaptors (110 – 240 V AC to 15 V DC) 1x Quickstart guide with Digital Passport 1 x Installation manual 1 x Small parts |
| EAN | 4260423860902 |

Current System Requirements

| | |
|-------------------------|---|
| System requirements | Mobile device: Newest iOS on iPhone/iPad, newest Android on Smartphone/Tablet Internet: High-Speed Landline Broadband Internet connection, DSL, cable or fiber optic, no socks or proxy server Network: Ethernet Network, with DHCP |
| Supported door stations | Any DoorBird IP Video Door Station |

DISPLAY

| | |
|------------|-------------------|
| Dimensions | 4" True Color LCD |
| Touch | Yes, capacitive |
| Resolution | 800 x 480 px |
| IPS | Yes |

Audio

| | |
|------------------|--|
| Audio components | Speaker and microphone, echo and noise cancellation (AEC, ANR) |
| Audio streaming | Two-way |

Network

| | |
|----------|----------------------|
| Ethernet | PoE 802.3af Mode-A |
| Wi-Fi | 802.11 b/g/n 2.4 GHz |

INTEGRATED WIRELESS MODULES

| | |
|------|----------------------|
| WiFi | 802.11 b/g/n 2.4 GHz |
|------|----------------------|