



8" High-Quality In-Ceiling Speaker

80 F/X-LS

SKU: 23818 UPC: 747192000000

Never sacrifice professional audiophile features and performance when you can have it all, even on a budget. Award-winning technologies and high quality materials come together with purpose-designed engineering in the Vanishing F/X®-LS line of "invisible" in-ceiling surround-channel speakers. Customized audio controls give you more placement flexibility for optimum surround effects, and maximum interior design wow-factor. Use the space previously taken by speakers to add seating or wall treatments!

Features

- Use the customized imaging toggle to easily optimize surround effects in any room setup; choose the "Solid" setting for more localized effects, and the "Diffuse" setting for greater rear channel ambience.
- Vanishing Series built-in speakers feature our exclusive wafer-thin Sheer-Grille, a magnetically-secured grille that protrudes only 7mm from its surroundings. Sheer-Grilles have nearly transparent, ultra-small perfs, and are acoustically inert, for dynamic, unimpeded sound and more uniform coverage, even in larger rooms.
- Painted to match your Dacor, Vanishing Series built-in speakers are virtually indistinguishable from their surroundings.
- Dual offset ring radiator tweeters extend top-end response for incredible details and realistic imaging.
- Vanishing Series LS speakers are timbre-matched to Polk LSi speakers to insure utterly seamless blending from speaker to speaker in systems that combine traditional and built-in speakers.
- Dual bandpass bass ports are highly efficient in small enclosures, and smoothly funnels the angled woofer's low frequencies down around the driver array, eliminating "chuffing," so your small, practically invisible in-ceiling speakers achieve superior full-range blending and broad coverage with surprisingly deep bass.
- Easy one-cut, drop-in installation puts built-in audio within reach, with Perfect Fit templates, a precision flange, and (available) pre-construction brackets; achieve secure, vibration-free efficiency with a simple turn of the patented Rotating Cam system.

Quantity in Package Pair Tweeter Ring radiator Aimable Tweeter No Woofer Composition Aerated Polypropylene Woofer Surround Rubber Moisture-resistant No Connector Type Spring post Bi-Amp Inputs No Built-in Back-box No Labor Warranty Lifetime Tweeter Size .75 Midrange Size --- Speaker Shape Round Woofer Size 8 Cutout Width 9.375 Cutout Height 9.375 Power Range (Watts) 10-125 Sensitivity 88 dB Impedance (Ohms) 8 Frequency Response 45-29kHz Parts Warranty Lifetime