



Standard Mounting Post

1200-045

SKU: 4736 UPC: 1200-045

Several styles of mounting posts are available from DKS. Heavy-duty and designer style posts are typically used with the larger telephone entry systems and are available in gooseneck styles for vehicular traffic or straight styles for walk-up pedestrian use. The mounting kiosks are ideal for walk-up pedestrian applications and are designed for DKS flush mount telephone entry systems (80 Series only). Both the designer style post and the walk-up kiosk include an accessory compartment that can house accessory transformers, surge suppressors and a radio receiver. Additionally, the designer style post has an optional light tower that can be added to them. The standard posts are used with card readers, keypads and smaller access control devices. A dual-height style is also available for applications that have both vehicular and truck traffic.

Features

STANDARD POST

- Pad mount or in-ground mount styles available.
- Constructed from 2 x 2 steel.
- 43-inches tall to center of mounting plate (pad mount P/N 1200-045).
- Sweeps out approximately 13-inches.
- Pad mount style includes mounting plate and mounting plate cover.
- In ground mount unit (P/N 1200-046) is 65.5-inches overall length.
- Standard posts are not suitable for use with 1833, 1834, 1835 or 1837 systems.

HEAVY-DUTY STYLE POST

- Pad mount. In-ground adapters are available.
- Constructed from 4 x 4 steel.
- Gooseneck offset style (P/N 1200-037) is 49-inches to the top of the mounting plate and angles out approximately 14-inches.
- Straight style (P/N 1200-050) is 57-inches to the top of the mounting plate.
- Small offset gooseneck style (P/N 1200-036) is 41.75-inches to top of small mounting plate. Not for use with 1833, 1834, 1835 or 1837 systems.

DESIGNER STYLE POST

- Pad mount. In-ground adapters are available.
- Constructed from 4 x 8 steel.
- Offset style (P/N 1200-086) is 49.625 -inches to the top of the mounting plate and angles out approximately 14-inches.
- Straight style (P/N 1200-085) is 58.625-inches tall, 56.625-inches to the top of mounting plate.
- Accessory compartment includes four (4) 115 VAC convenience outlets and space for up to three (3) surge suppressors and an RF receiver.

Light tower - 4 x 8 steel (45 Lbs) All adapters are 24 inches tall sized to match their respective posts