



8" Vanishing Series In-Ceiling Speaker

V80

SKU: 23822 UPC: 747192000000

The Polk Audio V80 In-Ceiling Speaker AW4080 is designed with excellence. This speaker includes an ultra-thin non-obtrusive design. It is the perfect choice for a modern home. With Klippel Distortion Optimization for exemplary motor structure, voice coil alignment, and suspension, this in-ceiling speaker delivers the best performance at any volume level. Polk's Wafer-thin Sheer Grille makes for a seamless finish after installation. Not only that, Polk's exclusive lightweight Dynamic Balance® Polypropylene Cones bring spectacular midrange clarity, punchy bass, and high efficiency.

Features

- Klippel Distortion Optimization motor structure, voice coil alignment, and suspension
- Polk's Wafer-thin Sheer Grille
- Polk's exclusive lightweight Dynamic Balance
- Polypropylene Cones
- midrange clarity, punchy bass, and high efficiency.

Connections Connector Type: Gold Plated Push Connectors Construction Tweeter Composition: Silk Dome Driver Component Size: 8" Dimensions Diameter: 9.38" Mount Depth: 9.38" Other Sold As: Each Specifications Sensitivity: 90 dB Frequency Response: 30Hz - 27kHz Styling Color: White Overall Total Pieces 1 Accessories Included Accessories (1) Polk's Wafer-thin Sheer Grille - White, Paintable Optional Accessories (1) PB LC80i - Pre-Construction Bracket - Sold Separate, (1) Fire-Rated Back Box - Sold Separate, (1) Square Sheer Grille - White, Paintable - Sold Separate Shipping Cartons Carton 1 6.5" (16.51 cm) h x 12.25" (31.12 cm) w x 12.5" (31.75 cm) d - 5 lbs (2.27 kg) Warranty Lifetime Warranty Yes In-Ceiling Speaker Quantity Included 1 Depth 4.125" (10.48 cm) Driver Complement (1) 8" (20.32 cm) d (Round) Composite Polymer Cone with Butyl Rubber Surround - Mid/Woofer, (1) 1" (2.54 cm) d (Round) Swivel Mount, Silk Dome - Tweeter Grille Dimensions 11.125" (28.26 cm) diameter In-Ceiling Mount Shape Round Dimensions 9.375" (23.81 cm) diameter Flush Mounting Depth 3.625" (9.21 cm) - Audio Quality Total Frequency Response 30 Hz ? 27 Hz Nominal Impedance 8 ohms Sensitivity (1 watt @ 1 meter) 90 dB Lower and Upper -3dB Limits 45 Hz ? 25 Hz External Amplifier Recommended Amplifier Power Per Channel 10 watts - 100 watts Inputs Speaker Inputs (1) Pair of Push Connectors - Gold Plated Misc. Specs Frequency Response 30Hz - 27kHz Enclosure Material Polypropylene Outdoor Approved No Manufacturer Warranty 5 Year Parts & Labor Bi Amp Inputs No Input Power Range 10-100 Watts Speaker Connector Type Spring Clips RMS Power Handling 100 Color Black Enclosure Type Bass Reflex Impedance 8 ohms Sensitivity 90 Depth (in.) 3.63 Height (in.) 9.375 Video Shielded No Width (in.) 9.375