



## Classic Flush-Mount IP Video Intercom - Stainless Steel

423867550

SKU: 65362    UPC: 4260423867550

DoorBird is the smart solution for your house entrance. Simply connect your DoorBird IP Video Door Station to your smartphone and talk to your visitor – anywhere you are. The IP Video Door Station can be used as a stand-alone unit or can be integrated into an existing Smart Home platform. Even existing classic installations such as an electric door opener can still be used and controlled via the DoorBird App.

### Features

- Video intercom including flush-mounting housing
- LAN connection (PoE capable)
- 2-way audio
- Ultra-wide angle lens, 1080p, night vision, IR LEDs
- 4D motion sensor
- Keypad
- Intercom with 1 freely configurable bistable switching relay

Open API • Local interface for integration with third-party systems and SIP Video and audio call • On smartphones, tablets (iOS, Android), IP and landline phones (SIP) Smart Transmission Mode (STM) • Real-time audio / video communication, optimized for mobile devices via WiFi, 3G, 4G, 5G Smart Home & NVR compatible • Control4, Loxone, Crestron, Synology, AVM FRITZ!Fon, URC, QNAP, RTI, ELAN, Fibaro, Bang & Olufsen and others Automatic door buzzer • For use in medical offices and office environments Free visitor history • Store still images for free, optional video recording available Individual action schedules, e.g.: • Trigger relay 1 for automatic door release Mo-Fr from 9 am until 4 pm when the call button is pressed • 4D motion sensor switches on external lamp between 9 pm and 6 am Geofencing • Automatic door and gate opening when returning home Night vision • With 12 Infrared LEDs HDTV Video • Ultra wide-angle, hemispheric lens, 200° Light sensor • For night vision mode One freely configurable bistable latching relay • Control one door or gate via App • Status configurable via App: temporary or permanent circuit Easy self-install • Quick installation via QR code scan Configurable call button • With backlit nameplate Motion sensor with 4D technology • Distance up to 6 m (19,7f) adjustable via App (interval: 1 m"/"%3.3f) Noise reduction and echo cancellation (AEC, ANR) Keypad Module • Configurable via App • More than 1000 individual PIN codes • Individual events (e.g. switch a relay, HTTP(s) request) Easy connection to the network • Connection via network cable (PoE, network data) or bell wire via 2-wire transformer Microphone • Clear voice transmission