



## 8" Vanishing Series In-Wall Speaker

V85

SKU: 23820    UPC: 747192000000

Klippel Distortion Optimization for perfect motor structure, voice coil alignment, and suspension, delivering the best performance at any volume level. Virtually invisible installations with Polk's Wafer-thin Sheer Grille. Polk's exclusive lightweight Dynamic Balance® Polypropylene Cones deliver spectacular midrange clarity, punchy bass, and high efficiency.

### Features

- Polk's wafer-thin Sheer-Grille with ultra-small .6mm perf attaches magnetically to fit flush (acoustically inert).
- 1" silk dome tweeter for crisp, clear imaging.
- 8" Dynamic Balance driver with polypropylene cone and rubber surround for smooth, consistent frequency response.
- Polk patented Rotating Cam System ensures secure, vibration-free installation.
- Fire-rated enclosure available.

OVERALL Total Pieces: 1 Included Accessories (1) Polk's Wafer-thin Sheer Grille - White, Paintable Optional Accessories (1) PB 85 - Pre-Construction Bracket - Sold Separate SHIPPING CARTONS Carton 1 6.5" (16.51 cm) h x 12" (30.48 cm) w x 16" (40.64 cm) d - 6 lbs (2.72 kg) WARRANTY Lifetime Warranty: Yes VANISHING V-SERIES IN-WALL SPEAKER Qty Included: 1 (1) 8" (20.32 cm) d (Round) Composite Polymer Cone with Butyl Rubber Surround - Mid/Woofer (1) 1" (2.54 cm) d (Round) Swivel Mount, Silk Dome - Tweeter Grille Dimensions 10.5" (26.67 cm) h x 14.375" (36.51 cm) w IN-WALL MOUNT Shape: Rectangle Dimensions 12.75" (32.39 cm) h x 8.75" (22.23 cm) w Flush Mounting Depth 3.125" (7.94 cm) - Total Frequency Response 30 Hz â†' 27 Hz Nominal Impedance 8 ohms Sensitivity (1 watt @ 1 meter) 90 dB Lower and Upper -3dB Limits 45 Hz â†' 25 Hz EXTERNAL AMPLIFIER Recommended Amplifier Power Per Channel 10 watts â†' 125 watts