



## 6.5" In-Ceiling Speaker

C165

SKU: 62665

Monitor Audio C165 Ceiling Speakers incorporate a 6.5 inch bass driver and Monitor Audio's signature C-CAM gold dome tweeter to provide high-performance sound, ease of drive, and wide frequency response and dispersion. Optimum imaging and set-up are established via a pivoting tweeter and high-frequency (+3dB / 0dB / -3dB) level adjustment.

### Features

- 2-way design with pivoting C-CAM tweeters (15 degrees of play).
- High overall efficiency.
- High-frequency level adjustment (3dB).
- Audio match with BR-CP, Radius-CP, Climate 10 and Bronze BR and Radius Series hi-fi speakers.
- Our innovative Tri-Grip® fixing system is easier to install than conventional clamping schemes but provides three times the surface area and a better surface seal, maximising bass response and mid-range clarity.
- Magnetic and easily removable steel grille.
- Paint-able surface to blend with the living environment. Additional scrim material is provided for trouble free painting.
- Fire retardant to UL-94 VO rating.
- Splash and humidity proof for installation in shower room or pool areas.
- Features dust protection cover that is designed to prevent the ingress of dirt or dust into the driver and crossover.

Frequency Response 60 Hz - 25 kHz Nominal Impedance 6 ohms Sensitivity (1W@1M) 5 dB Maximum SPL 4 dBA Power Handling (RMS) 65 W Recommended Amplifier Requirements 20 - 65 W Drive Unit Complement 6 1/2" MMP Ilcone bass driver 1" C-CAM pivoting Gold Dome tweeter Adjustment Controls HF Level Switch (+3 dB / 0 dB / -3 dB) Overall Diameter (Including Grille) 250 mm (9 13/16") Overall Depth (Including Grille) 120 mm (4 3/4") Mounting Depth 116 mm (4 9/16") Cut-Out Hole Diameter 211 mm (8 1/4") Optional Square Grille - Outer Dimensions 249 x 249 mm (9 3/16") Fixing Type 3 position Tri-Gripdog fixings Construction Material Mineral filled ABS, RoHS compliant Weight 92 kg (4 lb 4 oz) Pre-Construction Bracket CB6 Pre-Construction Bracket (Purple) Back Box CCBOX-R/ CMBOX-R