



3MP WDR EXIR Outdoor Turret Camera

DS-2CE56F7T-VPIT3Z

SKU: 1004 UPC: 813908000000

The Hikvision DS-2CE56F7T-VPIT3Z 3 MP WDR Vandal-Resistant EXIR Dome Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing RG6 coaxial cable, eliminating the need to run new cables for high definition video. EXIR is Hikvision's proprietary IR extended range technology, which has a range of 66 feet (20 meters). Smart IR varies IR output based on the zoom setting. True 120 dB WDR (Wide Dynamic Range) ensures images will be optimal, no matter what the lighting conditions. This camera also features a range of Smart functions, including line crossing, intrusion, and region entrance and exit, benefitting users with great improvements on security efficiency and, more importantly, with key events and objects being recorded for further forensic needs. It is an outdoor IP66 camera that supports a wide temperature range.

Features

- 3 Megapixel high-performance CMOS
- Analog HD output, up to 3MP resolution
- 2.8-12mm motorized vari-focal lens
- True Day/Night
- OSD menu, DNR, Smart IR
- True WDR, up to 120dB
- EXIR technology, up to 40m IR distance
- IP66 weatherproof & vandal proof
- Up the Coax(HIKVISION-C)

Camera Image Sensor 3MP CMOS Image Sensor Effective Pixels 2052(H)*1536(V) Min. illumination 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR Shutter Time 1/25s to 1/50,000s Lens Motorized VF lens; 2.8 - 12 mm @ F1.2 Lens Mount 1/4" Day & Night ICR Angle Adjustment Pan: 0°- 340°; Tilt:0°- 75°; Rotate: 0°- 355° Synchronization Internal Synchronization WDR 120dB Video Frame Rate 1920x1536@18fps HD Video Output 1 Analog HD output S/N Ratio 62dB Menu AGC Support D/N Mode Color/BW/SMART White Balance ATW/ MWB BLC Support Functions Wide Dynamic Range, Digital noise reduction, Digital zoom(62x), Mirror, Defect pixel correction, SMART IR General Operating Conditions -40 °C - 60 °C (-40 °F - 140 °F), Humidity 90% or less (non-condensing) Power Supply 12 VDC±15%; -A: 12 VDC/24 VAC±15% Power Consumption Max. 4.5W; -A: Max. 6.5W Protection Level IP66 IR Range Up to 40m Impact Protection IK10 Communication Up the coax, Protocol: HIKVISION-C (TVI output) Dimensions 145.2mmx124.1mm (5.72"x4.89") Weight Approx. 1600g (3.53lb)