



Standalone Metallic RFID Reader Controller – Vertical Mount

SMK-V

SKU: 12614

SMK-V is an outdoor IP65-rated vandal-resistant metallic RFID reader with a back-lit keypad. SMK-V has a built-in 12V relay contact which can be connected directly to either an electric strike or magnetic door lock.

For the highest level of security and programming flexibility, SMK-V also has a built-in Wiegand-Out port which can be connected to most any access control panel (including ZKAccess C3 and InBio door controllers).

SMK-V comes standard with a built-in ZKAccess 125 KHz 26-bit RFID card reader. Mifare card reader option available.

Features

- IP65-rated vandal-proof metallic enclosure
- Standard ZK 125 kHz 26-bit card reader.
- Optional Mifare card reader available.
- Relay outputs for electric lock and alarm
- Auxiliary inputs for door status sensor and exit switch

Keypad Blue back-lit, Numeric keys 0-9, Function keys *, #, Bell LED indicator blue & red ID Card Capacity 1,000 cards Log Capacity N/A Communication N/A Standard Functions Single and dual-factor ID card and password authentication Access Control Hardware Interface Connects 3rd Party Electric Strike or Magnetic Lock, Door Sensor, Exit Button, Alarm Wiegand Interface Wiegand-Out port Optional Functions Built-in Mifare Card reader Power Supply 12V DC, 750mA Operating Temperature -4F° to 122F° Operating Humidity 20% - 80% Dimensions (HxWxD) Model SMK-V is 6.3 x 2 x .8 inches / Model SMK-H is 4.7 x 3.4 x .8 inches