



2-Door Access Control Panel with Biometrics

ATLAS260 BUN

SKU: 25918

Two-door Atlas Bio Series Access Control panel is designed & engineered in the U.S. Atlas panels are fast & simple to install because they require no software. Instead, the panels have an embedded full-featured access control web application. Atlas panels also use minimal wiring because they support both Power over Ethernet (PoE) and Wi-Fi communication. Atlas Bio Series Access Control panels support biometric readers, including fingerprint recognition.

There are 3 options when ordering Atlas panels:

- 1) individual panels can be ordered as spares or replacements;
- 2) as part of a €œbundle (including a metal enclosure & power supply) or
- 3) as part of a €œkit (including a bundle, fingerprint readers, fingerprint enrollment reader and request to exit buttons).

Features

- **Advanced Access Control** Built-in Web Application provides advanced access control features including User Enrollment & Management, Door Control & Monitoring, Lockdown, Reporting, Maps, Anti-Passback, First-Card Opening, Multi-Card Opening, Card Design and Duress PINs.
- **Door Control** User-programmable auxiliary relays can be used to control lights, alarms, annunciators, intrusion detection panels, additional locking devices, or any other external electrical device which can be controlled by a switch.
- **Capacity** 1 Primary panel can support up to 20 Secondary panels. Maximum 84 doors can be supported when using all 21 panels. Each Atlas Bio Series panel can store up to 5,000 users transactions plus unlimited archive downloads.
- **Power** Atlas Bio Series uses a 12V DC 3A power supply and also supports Power over Ethernet (PoE).
- **Choice of Readers** Atlas Series supports ZKAccess KR series & any 3rd-party readers which communicate with Wiegand or OSDP communication protocols.
- **Communication** Atlas Bio Series panels communicate securely over wired & wireless TCP/IP networks using SSL/TLS. Supported browsers include Google Chrome, Mozilla Firefox and Microsoft Edge.
- **Mobile App** Numerous convenient features include: remotely unlocking doors, universal lockdown & recovery, access to events & alarms, adding/modifying users.
- **Lowest Total Cost of Ownership** Atlas Series panels come in several models, to suit different project needs and reduce the cost of unused capacity. Easy-to-use embedded Web Application gets you up and running quickly. Firmware is field upgradeable, allowing your system to stay current with the latest features and security enhancements.

Capacity: Users 5,000 Events 10,000 Browsers Supported: Chrome Firefox Edge Safari Types of Readers Supported: ZKTeco KR Series readers FR1500-A-ID 3rd party 125kHz & 13.56MHz readers Wiegand OSDP RS-485 readers Others upon request Communication: TCP/IP Wiegand OSDP Number of Inputs: 5 (2 Exit Button, 2 Door Sensor, 1 Aux) Number of Outputs: 3 (2 Form C relay for lock and 1 Form C relay for Aux output) Weight: 10 lbs (4kg) Recommended Power: 12V DC, 3A (PoE) Dimensions: 14in X 2.5in. X 12in 380mm(L) X 80mm(W) x 280mm(H)