



5MP IP Full Color Turret Camera

K-CTIP5MPFW

SKU: 113403

Monitor an outdoor area with the ColorVu 5MP Outdoor Analog HD Turret Camera from Karbon Vision. This camera uses a 5MP progressive scan CMOS sensor to transmit 2592 - 1944 resolution video at 20 fps. A built-in spotlight provides up to 65' of illumination. The camera's 2.8mm fixed lens delivers a 94.8° horizontal field of view. Built-in true motion detection for push notification of actual movement to minimize false alarms. Also has an alarm output.

This turret camera is housed in an IP67-rated enclosure that is suitable for outdoor use.

Features

- 5MP (2592 - 1944) H.265 full real-time coding
- Max. resolution: 2592 - 1944
- 24/7 full-color imaging
- 20 ~ 30m white light view distance
- 3D DNR, True WDR, HLC, BLC, Defog, and ROI coding
- Support image distortion correction
- Built-in micro SD card slot, up to 256GB
- DC12V/PoE power supply
- IP 67 ingress protection
- Support three streams
- Support remote monitoring by smartphones & tablet PCs
- with iOS and Android OS
- Intelligent analytics

Camera Image Sensor 5 MP CMOS Signal System PAL/NTSC Frame Rate; PAL: 5MP@20fps, 4MP@25fps, 4MP@12.5fps, 1080p@25fps; NTSC: 5MP@20fps, 4MP@30fps, 4MP@15fps, 1080p@30fps Resolution 2592 (H) x 1944 (V) Min. Illumination 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR Shutter Time; PAL: 1/12.5 s to 1/50, 000 s; NTSC: 1/15 s to 1/50, 000 s Lens 2.8 mm, 3.6 mm fixed lens Horizontal Field of View 94.8° (2.8 mm), 80.1°(3.6 mm) Lens Mount M12 Strobe Light Alarm Yes Day & Night ICR WDR Digital WDR Angle Adjustment Pan: 0° to 360°, Tilt: 0° to 75°, Rotate: 0° to 360° Menu White Light Alarm/Off Image Mode STD/HIGH-SAT AGC Yes Day/Night Mode Auto/Color/BW (Black and White) White Balance Auto/Manual AE (Auto Exposure) Mode DWDR/BLC/HLC/Global Noise Reduction 2D DNR Language English Functions Brightness, Sharpness, Mirror, Smart IR Interface Video Output 1 HD analog output Alarm 1 alarm out General Operating Conditions -40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensing) Power Supply 12 VDC ± 25% Power Consumption Max. 3.5 W Ingress Protection IP67 Material Enclosure: Plastic Main body: Metal IR Range Up to 20 m PIR Angle and Range Angle: 110°, Range: 11 m White Light Range Up to 20 m