



## 8 Fused Outputs CCTV Power Supply

ALTV248600UL3

SKU: 779    UPC: 782240000000

ALTV248600UL3 provides 24VAC or 28VAC distributed via Eight (8) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories. Factory installed 3-wire line cord.

### Features

Secondary fuse rated @ 15 amp/32V. AC power LED. Power ON/OFF switch. Spare fuses provided. (all models w/primary and/or secondary fuses). Factory installed 3-wire line cord.

Input: 115VAC, 50/60Hz, 5.4 amp. Output: Eight (8) fuse protected outputs. 24VAC @ 25 amp (600VA) supply current (3.125 amp per device, 3.5 amp max.) or 28VAC @ 20 amp (560VA) supply current (2.5 amp per device, 3.5 amp max.). Outputs are rated @ 3.5 amp. Surge suppression. Electrical: Operating temperature: 0° C to 49° C ambient. BTU/Hr.: - 24VAC: 307.09 BTU/Hr.; - 28VAC: 286.62 BTU/Hr Electrical (cont<sup>TM</sup>d): System AC input VA requirement: 621VA. Mechanical: Enclosure Dimensions (H x W x D approx.): 13.5" x 13" x 3.25" (343mm x 330mm x 83mm) Product weight (approx.): 22.2 lbs (10.1 kg). Shipping weight (approx.): 23.2 lbs (10.5 kg).