



Classic Surface Mount

1812-081

SKU: 5465 UPC: 1812-081

The model 1812 is a unique telephone intercom system that allows homeowners to use their telephone as an intercom to speak to a guest at a front door or gate without the necessity to pay for an additional telephone line at their home. With its "intercom mode" programming feature, the 1812 can also be connected to a PBX or KSU type system, making it ideal for small businesses to control access through a single door or gate. Visitors are easily identified by voice communication and can be granted or denied access directly from a touch-tone telephone. The 1812 is available in surface, wall and flush mount designs.

Features

- Distinctive double ring identifies visitor calls from regular calls.
- Call waiting.
- Call forwarding.
- 3 preprogrammed call out telephone numbers.
- "Do Not Disturb" time zone.
- Hold open time zones.
- Built-in time clock.
- Entry code time zone.
- "Flash" entry code.
- LED lighted faceplate.
- 2 relays for door/gate control.

OPTIONS:

Surface or flush mount - specify which. Stainless steel housing (surface mount only).

Hands free, full duplex digital audio circuit. Connects in series with the residential phone line. By-pass switch provided. EEPROM Memory Chip. Stores up to 3 call forwarding numbers. Full duplex communication. 50, 4-digit entry codes. 24 VAC, 20 VA (250 ma) power transformer provided. FCC (US): DUF6VT-12874-OT-0 DOC (CAN): 1736 4507 A Complies with UL 294; ETL Listed. Surface mount dimensions: 6.13"H x 10"W x 5.25"D. Flush mount dimensions: 9.13"H x 11.88"W x 4.5"D.