



D1101V Surface-Mount IP Video Intercom - Stainless Steel

423866744

SKU: 65350 UPC: 4260423866744

A modern doorbell for home or office and stylish member of the brand new family of Doorbirds. As well as a refined and sophisticated look, this model introduces some new functionality. Such as Bluetooth for access control (future firmware update), 1080p Camera, Sony image sensor, and improved audio quality. And it looks so elegant!

For single-family houses and commercial buildings with 1 unit1 Call Button

Features

- Video intercom including surface-mounting housing
- WiFi / LAN connection (PoE capable)
- 2-way audio
- Ultra-wide angle lens, 1080p, night vision, IR LEDs
- 4D motion sensor
- Intercom with 1 freely configurable bistable switching relay

Front Panel	3 mm (0.12 in) For further materials and colours see material board and Online Shop.
Mounting Housing (backbox)	Polycarbonate
Mounting Type	Surface-mounted, flush-mounted version sold separately
Call button	Illuminated
Nameplate	Plastic Metal cover plate and engraving available separately
Power supply	15 V DC (max. 15 W) or Power over Ethernet (PoE 802.3af Mode-A)
Weight	405 g
Connectors	LAN/PoE (T+, T-, R+, R-) • Bistable latching relay, max. 1-24 V DC/AC, 1 A, e.g. for electric door opener • External input for external door opener button • 15 V DC input (+, -), max. 15 W • Relays can be expanded / detached with DoorBird I/O Door Controller
Protection Class	IP65, IK08
Approvals	CE, UKCA, FCC, IC, RoHS, REACH, WEEE, Wi-Fi CERTIFIED™

Dimensions	151,9 x 65 x 32 mm (H x W x D) 5.98 x 2.56 x 1.26 in (H x W x D)
Operating Conditions	-25 to +55°C / -13 to 131°F Humidity 10 to 85 % RH (non-condensing)