



2MP IR Bullet Camera

ANO-L6012R

SKU: 119513 UPC: 8801090000000

2MP IR Bullet Camera

Features

- 2 megapixel (1920 x 1080) resolution
- 2.8mm lens w/ 113.7° HFoV
- 30fps@ all resolutions (H.265/H.264)
- H.265/H.264, MJPEG codec supported, Multiple streaming
- Day & Night (ICR), WDR (120dB)
- Defocus detection, Directional detection, Motion detection, Enter/Exit, Tampering
- Micro SD/SDHC memory slot (Max. 32GB), PoE
- Hallway view, WiseStream II support
- IR viewable length 30m
- IP66 support

Video Imaging Device 1/2.8" CMOS Resolution 1920x1080, 1280x960, 1280x720, 800x600, 800x448, 720x576, 720x480, 640x480, 640x360 Framerate 265/H.264 : Max. 30fps/25fps(60Hz/50Hz) MJPEG : Max. 10fps Illumination Color: 0.03Lux(F2.0, 1/30sec) BW : 0Lux (IR LED on) Lens Focal Length (Zoom Ratio) 8mm fixed focal Aperture Ratio 0 Angular Field of View H: 113.7° / V: 61.5° / D: 134.4° Object Distance 5m(1.64ft) Focus Control Fixed Operational Camera Title Displayed up to 15 characters Day & Night Auto(ICR) Backlight Compensation BLC, WDR, SSSDR Wide Dynamic Range 120dB Digital Noise Reduction SSNR Motion Detection 4ea, rectangular zones Privacy Masking 6ea, rectangular zones Gain Control Low / Middle / High White Balance ATW / AWC / Manual / Indoor / Outdoor LDC Support Electronic Shutter Speed Minimum / Maximum / Anti flicker (2~1/12,000sec) Video Rotation Flip, Mirror, Hallway view(90°/270°) Analytics Motion detection, Tampering, Virtual area(Intrusion/Enter/Exit), Virtual line(Crossing/Direction) Alarm Triggers Analytics Alarm Events File upload via FTP and e-mail Notification via e-mail SD/SDHC recording at event triggers IR Viewable Length 30m(98.43ft) Network Ethernet RJ-45(10/100BASE-T) Video Compression 265/H.264 : Main/High, MJPEG Smart Codec WiseStream... Bitrate Control 265/H.264: CBR or VBR MJPEG: VBR Streaming Unicast(6 users) / Multicast Multiple streaming (Up to 3 profiles) Protocol IPv4, IPv6, TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTCP, RTSP, NTP, HTTP, HTTPS, SSL/TLS, DHCP, FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, UPnP, Bonjour Security HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP) Application Programming Interface ONVIF Profile S/G/T SUNAPI(HTTP API) General Webpage Language English Edge Storage Micro SD/SDHC 1slot 32GB Memory 512MB RAM, 256MB Flash Environmental & Electrical Operating Temperature / Humidity -30°C ~ +55°C(-22°F ~ +131°F) / Less than 95% RH * Start up should be done at above -20°C(-4°F) Storage Temperature / Humidity -30°C ~ +55°C(-22°F ~ +131°F) / Less than 95% RH Certification IP66 Input Voltage PoE(IEEE802.3af, Class2) Power Consumption Max 6.4W, Typical 5.0W Mechanical Color / Material White / Plastic RAL Code RAL9003 Product Dimensions / Weight 78.0x262.0mm(3.07x10.31"), 390g(0.86lb) DORI (EN62676-4 standard) Detect (25PPM/ 8PPF) 1m(82.28ft) Observe (63PPM/ 19PPF) 0m(32.91ft) Recognize (125PPM/ 38PPF) 0m(16.46ft) Identify (250PPM/ 76PPF) 5m(8.23ft)