



HIKVISION®

2MP Turret IP Camera with 4mm

DS-2CD2322WD-I 4

SKU: 13655 UPC: 813908000000

The DS-2CD2322WD-I 2MP Outdoor Network Turret Camera with Night Vision & 4mm Lens from Hikvision has a 2MP 1/2.8" progressive scan CMOS sensor to capture 1920 x 1080 resolution video at 30 fps. EXIR technology delivers up to 100' of night vision. The 4mm fixed lens features a 90° horizontal field of view. Integrated PoE technology allows data and power to be transmitted over one cable.

This device is ONVIF-compliant for Profiles S and G, making it compatible with a wide range of surveillance products. It is housed in an IP67-rated enclosure that is suitable for outdoor use.

Features

- 2 Megapixel High Resolution
- Full HD1080p Video
- Dual Video Streams
- 2.8 mm, 4 mm, 6 mm Fixed Lens Options
- 120 db Wide Dynamic Range
- 3D Digital Noise Reduction
- Smart Features
- PoE (802.3af)
- Supports H.264+
- High Performance EXIR LED
- IR Range 30 Meters (~100 Feet)
- IP67 Protection

Camera Image Sensor 1/2.8" progressive scan CMOS Minimum Illumination 0.028 lux @ (Æ/2.0, AGC on), 0 lux with IR Shutter Speed 1/3 s to 1/10,000 s Lens Fixed, 2.8 mm (4 mm, 6 mm options) Angle of View 109° (2.8 mm), 90° (4 mm), 54° (6 mm) Lens Mount M12 Day/Night IR cut filter with auto switch Digital Noise Reduction 3D Digital Noise Reduction Wide Dynamic Range 120 dB Pan/Tilt/Rotation Pan: 0° to 360°, tilt: 0° to 75°, rotation: 0° to 360° Compression Standards Video Compression H.264+, H.264, MJPEG H.264 Type Main Profile Video Bit Rate 32 Kbps to 16 Mbps Dual Streams Yes Image Maximum Resolution 1920 x 1080 Frame Rate 30 fps (1920 x 1080), (1280 x 960), (1280 x 720) Image Settings Compression, color, saturation, brightness, contrast, sharpness, rotate mode, privacy mask Back Light Compensation Yes, zone configured Region of Interest (ROI) Yes Analytics Smart Features Line crossing detection, intrusion detection Network Network Storage NAS (supports NFS,SMB/CIFS), ANR Alarm Triggers Motion detection, line crossing detection, intrusion detection, tamper alarm, network disconnect, IP address conflict, storage exception Protocols TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RT SP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour Security Three level user authentication, password authorization, HTTPS and SSH certificate, IEEE802.1X, basic and digest authentication, watermark, IP address filtering, log-in lockout Standards ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI Interface Communication 1 RJ-45 10M/100M Ethernet port General Operating Conditions -30° C to 60° C (14° F to 140° F), humidity 95% or less (non-condensing) Power 12 VDC ±10%, PoE (802.3af) Power Consumption Maximum 7.5 W with ICR on IR Range 30 meters (~100 feet) Ingress Protection IP67 Dimensions 127 mm x 97.5 mm (5.0" x 3.8") Weight 670 g (1.5 lbs)