



## 4 Fused Outputs CCTV Power Supply

ALTV244UL

SKU: 777

ALTV244UL provides 24VAC or 28VAC distributed via four (4) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

### Features

- Secondary fuse rated @ 5 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.

Input: 115VAC, 50/60Hz, 0.9 amp. Output: Four (4) fuse protected outputs. 24VAC @ 3.5 amp (85VA) supply current (0.875 amp per device, 3.5 amp max.) or 28VAC @ 3 amp (85VA) supply current (0.75 amp per device, 3.5 amp max.). Outputs are rated @ 3.5 amp. Surge suppression. Electrical: Operating temperature: 0° C to 49° C ambient. BTU/Hr.: 42.99 BTU/Hr. Electrical (cont<sup>TM</sup>d): System AC input VA requirement: 103.5VA. Mechanical: NEMA1 Enclosure. Enclosure Dimensions (H x W x D approx.): 8.5" x 7.5" x 3.5" (215.9mm x 190.5mm x 88.9mm) Product weight (approx.): 6.4 lbs. (2.9 kg). Shipping weight (approx.): 7.0 lbs. (3.2 kg).