



2MP HD WDR EXIR Turret Camera

DS-2CE56D7T-ITMG

SKU: 7075 UPC: 842571000000

The DS-2CE56D7T-ITMG-2.8MM from Hikvision is a HD 1080p WDR EXIR outdoor turret camera, 2.8mm lens. It provides high definition analog output up to 1080p. TurboHD means that the analog signal can be sent over existing RG6 coaxial cable, eliminating the need to run new cables for high definition video. EXIR is Hikvision's proprietary IR extended range technology, which has a range of 66 feet (20 meters). Smart IR varies IR output based on the zoom setting.

Features

- 2 Megapixel high-performance CMOS
- Analog HD output, up to 1080P resolution
- True Day/Night
- OSD menu, DNR, Smart IR
- True WDR, up to 120dB
- EXIR technology, up to 20m IR distance
- IP66 weatherproof
- Up the Coax(HIKVISION-C)

Camera Image Sensor 2MP CMOS Image Sensor Signal System PAL/NTSC Effective Pixels 1928(H)*1088(V) Min. illumination 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR Shutter Time 1/25(1/30)s to 1/50,000s Lens 2.8mm, 3.6mm, 6mm optional Angle of View: 103°(2.8mm), 82.2°(3.6mm), 54°(6mm) Lens Mount M12 Day & Night ICR Angle Adjustment Pan: 0°- 360°; Tilt:0°- 75°; Rotate: 0°- 360° Synchronization Internal Synchronization WDR 120dB Video Frame Rate 1080p@25fps/1080p@30fps HD Video Output 1 Analog HD output S/N Ratio i¼ž62dB Menu AGC Support D/N Mode Color/BW/SMART White Balance ATW/ MWB BLC Support Functions Wide Dynamic Range, Digital noise reduction, Mirror, SMART IR General Operating Conditions -40 °C - 60 °C (-40 °F - 140 °F), Humidity 90% or less (non-condensing) Power Supply 12 VDC±15% Power Consumption Max. 5W Protection Level IP66 IR Range Up to 20m Communication Up the coax, Protocol: HIKVISION-C (TVI output) Dimensions 91mmx82.6mmx68.3mm (3.58"x3.25"x2.69") Weight Approx. 350g (0.77lb)