



D2101KV IP Video Door Station (Flush Mount) - Stainless Steel V2A

423869998

SKU: 17253 UPC: 4260423869998

Answer a door anywhere! Your clients can see and speak with visitors and open their door using a smartphone or tablet. With DoorBird, your clients never miss a visitor.

The DoorBird D2101KV is the ideal solution for single family homes and commercial properties that require an efficient access control solution. The D2101KV has an integrated keypad that selectively controls two built in bistable relays. Access control pin codes are created and managed via the DoorBird app. The built-in relays can also be controlled via the DoorBird app to allow the user to remotely grant access to visitors. The DoorBird IP Video Door Station can be used as a stand alone system or easily integrated into a smart home, CCTV, or control system. All DoorBird products are designed, developed, and manufactured in Berlin, Germany.

Features

- Surface- and flush-mount possible, housings sold separately
- LAN connection (PoE capable)
- 2-way audio
- Ultra-wide angle lens, 720p, night vision, 12 IR LEDs
- 4D motion sensor, RFID reader
- Keypad
- Intercom with 2 freely configurable bistable switching relays

Front Panel	3 mm (0.12 in) Available in brushed stainless steel V2A / V4A and V2A with bronze and titanium finish, DB 703, RAL 7016, Graphite Black (Raven Polar)
Mounting Type	Flush- or surface-mounted, mounting housing sold separately
Power supply	15 V DC (max. 15 W) or Power over Ethernet (PoE 802.3af Mode-A)
Call Button	Illuminated
Nameplate	Stainless Steel, Bell symbol, engraved through material for illumination, self-adhesive. Engravable metal nameplate sold separately

Keypad Module	<p>12 keys, illuminated, configurable via App, e.g.</p> <ul style="list-style-type: none"> • Individual PIN codes • Individual events (e.g. switch a relay, HTTP(s) request) • Individual schedules • Up to 500 PIN codes manageable • 30 most recent entries viewable in history
Weight	1510 g
Connectors	<ul style="list-style-type: none"> • RJ45, for LAN/PoE • Bistable latching relay #1, max. 24 V DC / AC, 1 Ampere, e.g. for electric door opener • Bistable latching relay #2, max. 24 V DC / AC, 1 Ampere, e.g. for electric door opener • External input for external door opener button • 15 V DC input (+, -), max. 15 W • Relays can be expanded / detached with DoorBird I/O Door Controller
Weather-proof	Yes, IP65
Approvals	IP65, CE, FCC, IC, RoHS, IK08, REACH, IEC/EN 62368, IEC/EN 62471
Dimensions	<p>351,5 x 131 x 49,6 mm (H x W x D) 13.84 x 5.16 x 1.95 in (H x W x D)</p>
Operating conditions	<p>25 to +55°C / -13 to 131°F Humidity 10 to 85 % RH (non-condensing)</p>