



**Russound**

## Landscape Speaker

AW4-LS-BR

SKU: 16575    UPC: 612935000000

The AW4-LS-BR loudspeaker offers an elegant, scalable platform for providing high-quality audio to any outdoor area in even the harshest environmental conditions. Specially designed to withstand both extreme heat and cold, the speakers work great from the humid, hot conditions of summertime in Florida to the bone-chilling cold of a Minnesota winter. The key component of the Russound landscape audio system is the AW4-LS-BR, a compact 4 2-way design satellite speaker that can be mounted anywhere in an outdoor space, from ground level to the treetops. Its small profile and subtle coloring allow it to blend into your landscape design while its high-quality audio complement can add a new dimension of sound to your outdoor living space and bring your favorite music to your back yard, patio, pool, or lanai. The AW4-LS-BR allows you to transform any outdoor space into an elegant, inviting space where the music you enjoy indoors can be easily enjoyed outdoors without the need for large and unsightly loudspeakers that clutter the view and limit your (and your landscape designer's) choices when designing your perfect outdoor living areas.

### Features

- Designed for excellent sonic performance in any outdoor space
  - Rust-proof aluminum grille and color-molded composite construction won't chip, peel, or fade over time
  - 120° vertical directional adjustment allows sound to be directed where desired in any installation
  - ASA-based material design for maximum UV protection and environmental endurance from -15°F to 160°F (-25°C to 70°C)
  - Flexible 70v/100v/8Ω design with adjustable tap settings for use in any application
  - Includes 11 mounting stake and waterproof wire nuts
  - Works with 1/2-threaded landscape lighting mounts for limitless mounting options
  - Five year limited warranty
- 
- Type: 2-Way Landscape Speaker
  - Woofer: 4" (102mm) PP Weatherproof Cone (rubber surround)
  - Tweeter: 3/4" (19mm) Marine Grade PEI Dome
  - Frequency Response: 80Hz - 20kHz
  - Impedance: 8Ω - 70/100V
  - Tap Settings: 70V – 2W, 4W, 8W, 16W, 32W; 100V – 4W, 8W, 16W, 32W; 8Ω Bypass
  - Recommended Power for 8-ohm systems: 20~100W RMS
  - SPL: 87dB @1w/1m
  - Dimensions: 5"dia x 7.6"L x 7.7H" (without stake) (12.7 x 19.3 x 19.6 cm)
  - Unit Weight: 3.6 lbs. (1.65 kg)