



2-Channel 75 Watt Dual Source Amplifier

P75

SKU: 16491 UPC: 612935000000

The P75 is a 2-channel dual source power amplifier with auto source switching. It features two audio line inputs with a loop out to another zone, receiver, or device from Line 2 source. This amplifier can be used for power upgrades in specific zones, for speaker selector or volume control systems.

The P75 is a Class A/B amplifier rated at 75 watts per channel into 4 ohms, and 60 watts into 8 ohms. With the Stereo/Bridge Mono switch in Bridge Mono position, both amplifier channels are combined for a higher-powered mono output. In Bridge mode, the P75 is rated at 160 watts of power into a single 8-ohm load.

Features

- Built for multi-speaker applications with volume controls
- Automatic switching between two sources with signal sensing
- Front panel volume and balance controls
- Channels are bridgeable to create one channel with 160 watts of power
- High-current, high-power output
- Auto-switching dual source inputs
- A/B speaker pair selection from front panel easily toggles output between 2 sets of speakers or zones
- Rear panel unswitched AC outlet
- 60 watts per channel at 8 ohms, 75 watts per channel at 4 ohms
- Bridgeable: 160 watts mono at 8 ohms for higher output for use with a subwoofer or outdoor speakers
- Frequency response: 10 Hz to 30 kHz
- Advanced thermal and short circuit protection
- Front panel volume and balance controls allows for control at the component instead of volume control or keypad
- Auto switching dual source inputs

Specifications: Minimum Frequency Response: 10 Hz Maximum Frequency Response: 30 kHz Impedance: 4 Ohm
Classification: AB Audio Channels: 2 RMS Output Power: 150 W Number of Analog Audio Inputs: 4 Operating Power
Consumption: 400 W Color: Black Green Compliant: Yes Green Compliance Certificate/Authority: WEEE