



8" Dipole / Bipole In-Ceiling Speaker

C380-FX

SKU: 29959

Monitor Audio C380-FX In-Ceiling Speaker

Features surround mode selection of dipole (diffuse sound) or bipole (direct sound) operation for super-discreet home theatre sound. Incorporates an 8-inch C-CAM RST bass driver 8-inch C-CAM bass driver and dual 1-inch C-CAM gold dome tweeters mounted at a precise fixed-angle for optimized performance. Optional square grille can be used with model.

Features

- ideal for an overhead surround effects channel in a home theater system
- dipole/bipole switch offers easy toggling between surround modes
 - dipole: gives you diffuse sound, ideal for when the speaker is placed to the side of the listening area
 - bipole: more direct sound, better for when the speaker is placed behind the listening area
- dual 1" gold dome C-CAM® (Ceramic-Coated Aluminum/Magnesium) tweeters for detailed sound
 - tweeters fire sound in different directions for wraparound sound effects
 - three-position tweeter level control cuts or boosts high-frequency output to ideally suit your room's acoustics
- 8" C-CAM woofer for smooth midrange and tight bass response
- unobtrusive frame and low-profile grille for discreet installation
- recommended amplifier power: 30-120 watts
- frequency response: 45-30,000 Hz
- sensitivity: 90 dB
- impedance: 6 ohms
- patented Tri-Grip® mounting system ensures maximum surface seal for better bass and midrange clarity
- paintable removable magnetic steel grille
- cutout diameter: 9-3/4"
- overall diameter: 11-1/4"
- mounting depth: 6-1/8"
- weight: 7 lbs.

Frequency Response 45 Hz - 30 kHz Nominal Impedance 6 ohms Sensitivity (1W@1M) 90 dB Maximum SPL 6 dB A Power Handling (RMS) 120 W Recommended Amplifier Requirements 30 - 120 W Drive Unit Complement 8" C-CAM cone bass driver featuring RST 2 x 1" C-CAM fixed angle Gold Dome tweeters Adjustment Controls HF Level Switch (+3 dB / 0 dB / -3 dB) Bipole / Dipole Switch with Additional 12v Trigger Switching Overall Diameter (Including Grille) 285 mm (11 1/4") Overall Depth (Including Grille) 161 mm (6 5/16") Mounting Depth 157 mm (6 3/16") Cut-Out Hole Diameter 247 mm (9 3/4") Optional Square Grille - Outer Dimensions 285 x 285 mm (11 1/4") Fixing Type 3 position Tri-Grip dog fixings Construction Material Mineral filled ABS, RoHS compliant Weight 2 kg (7 lb) Pre-Construction Bracket CB8 Pre-Construction Bracket (Green) Back Box CMBOX-R