



D204 IP Video Door Station Fence Assembling Edition

423860155

SKU: 8547

The DoorBird is a smartphone doorbell that communicates with remote devices via Wi-Fi or Ethernet connectivity, enabling two-way real-time audio talkback and HDTV video monitoring of visitors at the doorstep. The device may be set to deliver an instant push notification to a paired mobile device when the visitor presses the doorbell button, or if unexpected motion activity occurs within user-defined infrared monitoring zones within view of the camera. Also supports connection to a standard door chime.

How it works

Remove your existing doorbell. You will then see at least two wires in your wall. Connect these two wires to the DoorBird video door station to power it and mount it near to your door. Connect the DoorBird to your Internet router using WiFi or Ethernet cable. We use bank level encryption technologies. Done! You will now receive instant alerts (push notification) with sound on your smartphone or tablet if someone pushes the doorbell button, you can see and talk with your visitor in real-time.

Features

- May be paired with up to 8 iOS or Android devices.
- Generates a time-stamped log of visitor activity, accessible only to designated users.
- Supports integration with traditional door chime and door opener.
- Also integrates with DoorBird IP cameras for further home surveillance capabilities.
- Infrared LEDs permit PIR night vision up to 8 meters.
- HD Camera bears a 180° field of view, and provides VGA video at 30 fps.
- IP54 weather-proofing.

Bird Home Automation has announced that the DoorBird smartphone doorbell will soon support integration with Apple HomeKit.

Housing Front panel 3 mm (0,12 in) brushed Stainless-steel, galvanized steel laterals powder coated RAL 9007, door with cylinder lock and 2 keys Doorbell button Stainless-steel button with illuminated LED Ring Nameplate Illuminated Mounting type Fence assembly Power supply 15 V DC (power 110 - 240 V AC) or Power over Ethernet (PoE 802.3af Mode-A) Weight 12 kg Connectors Power, electric door opener/strike, door chime, door opener button, network Weather protection Yes, IP65 Approvals CE, IC, FCC, IP65 Dimensions 550 x 379 x 113 mm (H x W x D) 21,65 x 14,92 x 4,45 in (H x W x D) Operating conditions -20 to +40°C / -4 to 104°F Humidity 10 to 85 % RH (non condensing) Scope of delivery Video Door Station, front panel, fence assembly housing, power supply unit (world-wide, 110 - 240 V), DIN-Rail power supply sold separately, screw package, quickstart guide, 2 x 1m antenna extension cable, 2 x external antenna EAN 4260423860155 Warranty see www.doorbird.com/warranty