



6.5" Vanishing Series In-Wall Speaker

V65

SKU: 23823 UPC: 747192000000

Klippel Distortion Optimization for perfect motor structure, voice coil alignment, and suspension, delivering the best performance at any volume level. Virtually invisible installations with Polk's Wafer-thin Sheer Grille. Polk's exclusive lightweight Dynamic Balance® Polypropylene Cones deliver spectacular midrange clarity, punchy bass, and high efficiency.

Features

- Full-range dynamic audio from a low-profile speaker designed for a flush fit with your wall
- Silk dome tweeters set in a 15° swivel housing provide direct high-frequency control, excellent off-axis imaging, and more placement flexibility
- Innovative features and patented Polk Audio technology in a discrete, easy-to-install package
- Timbre-matched to the RTA Series

Connector Type: Gold Plated Push Connectors Tweeter Composition: Silk Dome Driver Component Size: 6.5" Mount Depth: 2.88" Sold As: Each Sensitivity: 90 dB Frequency Response: 32Hz - 27kHz Color: White (1) Polk's Wafer-thin Sheer Grille - White, Paintable (1) PB LC60i - Pre-Construction Bracket - Sold Separate (1) Fire-Rated Back Box - Sold Separate (1) Square Sheer Grille - Sold Separate Carton 1: 6.25" (15.88 cm) h x 10.75" (27.31 cm) w x 11" (27.94 cm) d - 4 lbs (1.81 kg) Lifetime Warranty: Yes Quantity Included: 1 Depth: 3.75" (9.53 cm) (1) 6.5" (16.51 cm) d (Round) Composite Polymer Cone with Butyl Rubber Surround - Mid/Woofer; (1) 0.75" (1.91 cm) d (Round) Swivel Mount, Silk Dome - Tweeter 9.625" (24.45 cm) diameter Shape: Round Dimensions: 8.188" (20.8 cm) diameter Flush Mounting Depth: 3.25" (8.26 cm) Total Frequency Response: 33 Hz - 27 Hz Nominal Impedance: 8 ohms Sensitivity (1 watt @ 1 meter): 89 dB Lower and Upper -3dB Limits: 50 Hz - 25 Hz Recommended Amplifier Power Per Channel: 10 watts - 100 watts (1) Pair of Push Connectors - Gold Plated RMS Power Handling: 125 Impedance: 8 ohms Height (in.): 12.75 Width (in.): 7.25