



Rugged Grade 1 Rim-Type Exit Device Push-to-Exit Bar

SD-962AR-36G

SKU: 27568 UPC: 676544000000

The ENFORCER Grade 1 Rim-Type Exit Device, when mounted on the inside of a door to block entry to a protected premises, securely locks the door from outside access while allowing users inside the protected premises to exit.

Features

- Pushbar is UL Listed for U.S. and Canada
- Heavy-duty ANSI Grade 1 steel construction
- Allows exit from inside while locked from outside
- Reversible non-handed design
- UL Listed, ANSI/BHMA A156.3 - (2008) requirements for Grade 1, UL 305
- For metal or wood doors up to 1³/₄" (44mm) thick
- A separate deadlocking latch prevents the use of credit cards or similar means to open the latch bolt
- Allen-type 1/4-turn dogging lock allows the exit device to be unlocked for extended periods of time
- Includes all needed hardware for typical installations
- Works with standard external door handle/lock devices such as the-962HL-4A(not included)
- Fits doors from 33" (84cm) to 48" (122cm) wide

Construction ANSI Grade 1 steel Door Type Up to 1-3/4" (44mm) thick, wood or metal Hand Type Non-handed Latch Bolt Stainless-steel, 3/4" (19mm) throw Dead Latch Stainless-steel 5/8" (16mm) Strike For 5/8" (16mm) stop Spring Stainless steel Chassis Plated steel Cover Plated zinc cast Rail Assembly Aluminum End Cap Plated zinc cast Dogging Allen-type dogging standard Dimensions 33"x8"x2-3/16" (838x203x56 mm) Weight 9-lb 12-oz (4.4kg)