

4K ULTRA HD™



peerless-AV™

65" UltraView UHD Outdoor TV

UV652

SKU: 19501 UPC: 735029000000

The UltraView UHD Outdoor TV is an all-season solution for outdoor entertainment and living. This outdoor TV is all weather rated, maintenance-free and has an operating temperature range of -22°F to 122°F. With 4K resolution and an IPS panel, the UltraView provides exceptional color and video quality from any viewing angle. The TV is also equipped with a High TNi panel, which allows for direct sunlight readability without the risk of isotropic blackout. The input compartment and DC power ports provide safe storage and power for small video equipment. Whether you want an outdoor TV above your backyard fireplace or by the pool, quality outdoor entertainment is now a reality with UltraView.

Features

- 4K LCD Display
- 500 NIT Brightness
- Operating Temperature: -22° to 122° F
- Rugged Aluminum Exterior w/IP55 Rating
- High TNi Panel Allows For Direct Sunlight Readability Without Isotropic Blackout
- Waterproof Universal Remote Can Control Up To 3 Additional Devices
- Play Media Directly from USB Flash Drive

Display Size: 65" Display Technology: IPS LCD Aspect Ratio: 16:9 Resolution: 3840 x 2160 Maximum Brightness: 500 cd/m2 HDR Compatibility: None Contrast Ratio: 1100:1 Response Time: 8 ms Refresh Rate: 60 Hz Viewing Angle (H x V): 89 x 89° Video System: NTSC / ATSC TV Tuner: Yes Connectivity Input Ports: 1 x 1/8" / 3.5 mm (VGA) 1 x 1/8" / 3.5 mm (Component/Analog Audio) 1 x 1/8" / 3.5 mm (Composite/Analog Audio) 3 x HDMI Type A (Digital Audio) 1 x DisplayPort (Digital Audio) 1 x DE-15/DB-15 (VGA) 1 x F-Type (Composite) Output Ports: 1 x TOSLINK Optical (Digital Audio) 1 x 1/8" / 3.5 mm (Headphone) Wi-Fi: None Bluetooth: None USB Ports: 1 x USB 2.0 (Service) 1 x USB (Version Unspecified) Control IR via 1/8" / 3.5 mm Input RS-232C via DE-9/DB-9 Convenience Virtual Assistant Support: None Media Player: BMP JPEG MP3 TXT WAV Supported Languages: English French Spanish Wall Mounting: 400 x 400 mm Remote Battery Type: 2 x AAA Environmental Operating Temperature: -22 to 122°F / -30 to 50°C Storage Temperature: -4 to 140°F / -20 to 60°C General AC Input Power 100 to 240 VAC, 50 / 60 Hz Certifications: FCC, UL, as per Manufacturer Dimensions: 59.11 x 34.51 x 4" / 150.14 x 87.66 x 10.16 cm Weight: 85 lb / 38.6 kg Packaging Info Package Weight: 108 lb Box Dimensions (LxWxH): 63.25 x 38.25 x 8.13"

KOA