



2MP Ultra Low-Light Exir Turret Camera

K2MPE-W

SKU: 17440

The Hikvision K2MPE-W 2 MP Outdoor Ultra-Low Light EXIR Turret Camera provides high definition analog output. TurboHD means that the analog signal can be sent over existing coaxial cable, eliminating the need to run new cables for high definition video. EXIR is Hikvision's proprietary IR extended range technology, which has a range of 130 feet (40 meters). The 2.8 mm, 3.6 mm, 6 mm lens options are optimized for viewing angles that fit any situation. True 120 db WDR (Wide Dynamic Range) ensures that ideal images are captured regardless of the lighting conditions.

Features

- 2.0 megapixel high-performance CMOS
- HD analog output, up to 1080p resolution
- 2.8 mm, 3.6 mm, 6 mm fixed focal lens
- True Day/Night
- 120 dB true WDR
- OSD menu, DNR, Smart IR
- EXIR 2.0, up to 20 m IR distance
- IP67
- Up the Coax (HIKVISION-C)

Camera Image Sensor 2.0 megapixel progressive scan CMOS Signal System PAL/NTSC Frame Rate PAL: 1080p@25fps NTSC: 1080p@30fps Resolution 1920 (H) x 1080 (V) Min. illumination Color: 0.005 Lux @ (F2.0, AGC ON), 0 Lux with IR Shutter Time PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s Slow Shutter Max. 16 times Lens 2.8 mm, 3.6 mm, 6 mm fixed focal lens Horizontal Field of View 103.5°(2.8 mm), 82.6°(3.6 mm), 54.4°(6 mm) Lens Mount M12 Day & Night IR cut filter Angle Adjustment Pan: 0°to 360°, Tilt:0°to 75°, Rotate: 0°to 360° Synchronization Internal synchronization WDR (Wide Dynamic Range) > 120 dB Menu AGC Support Day/Night Mode Auto/Color/BW (Black and White) White Balance ATW/MANUAL Privacy Mask ON/OFF, 4 programmable privacy masks Motion Detection 4 programmable motion areas Backlight Compensation WDR/BLC/HLC/OFF 3D DNR (Digital Noise Reduction) On Language English, Chinese Functions Brightness, Sharpness, Mirror, Smart IR Interface Video Output 1 HD analog output General Operating Conditions -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation) Power Supply 12 VDC±25% Power Consumption Max. 3.5 W Ingress Protection IP67 Material Metal IR Range Up to 20 m Communication Up the coax, Protocol: HIKVISION-C (TVI output) Dimensions 91 mm x 82.6 mm x 68.3 mm (3.58" x 3.25" x 2.69") Weight Approx. 350 g (0.77 lb.)